POLK 53819

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

5/14/2016

		Page 1 of 2
WELL I.D. LABEL# I	113159	
START CARD #	1024415	
ORIGINAL LOG #		

(1) LAND OWNER Owner Well I.D.					
First Name RODGER Last Name FITTS	(9) LOCATION OF WELL (legal description)				
Company WIGRICH FARMS	County POLK Twp 9.00 S N/S Range 4.00 W E/W WM				
Address 5835 WIGRICH RD					
City INDEPENDENCE State OR Zip 97351	Sec 2 SE 1/4 of the NW 1/4 Tax Lot 100				
(2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot				
	Lat ° ' "or DMS or DD				
Alteration (complete 2a & 10) Abandonment(complete 5a)	Tax Map Number Lot Lat " " or DMS or DD Long " " or DMS or DD				
(2a) PRE-ALTERATION Dia + From To Gauge Stl Plstc Wld Thrd	Street address of well Nearest address				
Casing:	5835 WIGRICH RD. INDEPENDENCE, OR. 97351				
	3633 WIGNICH RD. HADEI ENDENCE, OR. 77331				
Material From To Amt sacks/lbs					
Seal:	(10) STATIC WATER I EVEL				
(3) DRILL METHOD	(10) STATIC WATER LEVEL Date SWL(psi) + SWL(ft)				
Rotary Air Rotary Mud X Cable Auger Cable Mud	Date SWL(psi) + SWL(ft) Existing Well / Pre-Alteration				
Reverse Rotary Other	Completed Well				
(4) PROPOSED USE Domestic Irrigation Community	Flowing Artesian? Dry Hole?				
Industrial/ Commercial Livestock Dewatering	WATER BEARING ZONES Depth water was first found 20.00				
Thermal Injection Other	SWL Date From To Est Flow SWL(psi) + SWL(ft)				
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)	3/1/2015 20 40 2000 14				
Depth of Completed Well 50.00 ft.					
BORE HOLE SEAL sacks/					
Dia From To Material From To Amt lbs					
20 0 18 Bentonite Chips 0 18 24 S					
16 18 50 Calculated 18.17					
Calculated	(11) WELL LOG Ground Elevation				
How was seal placed: Method A B C D E	Material From To				
	Hard top soil 0 4				
X Other POURED AND PROBED					
Backfill placed from ft. to ft. Material	only crown etay				
Filter pack from ft. to ft. Material Size	Tight brown Sandy silt 8 20				
Explosives used: Yes Type Amount	Gray/brown sand 20 21				
· · · · · · · · · · · · · · · · · · ·	Loose gray/brown sand and gravel med-lg. 21 40				
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	Blue clay 40 50				
Proposed Amount Actual Amount					
(6) CASING/LINER					
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	RECEIVED BY OWRD				
● 16 × 1 48 .250 ● ×	NECEIVED BY OVIIIS				
● 16 48 50 .500 ● X					
● 16 48 50 .500 ● X	HIN 0 4 2010				
	JUN 2 4 2016				
Shoe Inside Outside Other Location of shoe(s) 50	SALEM, OR				
Temp casing Yes Dia From To					
(7) PERFORATIONS/SCREENS Perforations Method Mills knife					
Screens Type Material	Date Started 9/20/2014 Completed 3/1/2015				
Perf/ Casing/ Screen Scrn/slot Slot # of Tele/	(unbonded) Water Well Constructor Certification				
Screen Liner Dia From To width length slots pipe size	I certify that the work I performed on the construction, deepening, alteration, or				
Perf Casing 16 27 40 .375 3 364	abandonment of this well is in compliance with Oregon water supply well				
	construction standards. Materials used and information reported above are true to				
	the best of my knowledge and belief.				
	License Number Date				
(8) WELL TESTS: Minimum testing time is 1 hour					
	Signed				
	(handad) Water Wall Constructor Continues				
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification				
60 0 1	I accept responsibility for the construction, deepening, alteration, or abandonment				
	work performed on this well during the construction dates reported above. All work				
	performed during this time is in compliance with Oregon water supply well				
Temperature 56 °F Lab analysis Yes By	construction standards. This report is true to the best of my knowledge and belief.				
17 69	License Number 1629 Date 5/14/2016				
Water quality concerns? Yes (describe below) TDS amount I I From To Description Amount Units	1029				
	Signed JAMES GUNN (È-filed)				
	Contact Info (optional)				
	Contact fino (optional)				

WATER SUPPLY WELL REPORT continuation page

(5) BORE HOLE CONSTRUCTION

From

Material

Material

Size

From To

To

From

(8) WELL TESTS: Minimum testing time is 1 hour

Drawdown

+ From

Dia

Dia

Material

BORE HOLE

From

FILTER PACK

To

(7) PERFORATIONS/SCREENS

Dia

Perf/ Casing/ Screen

Screen Liner

Yield gal/min

From

(6) CASING/LINER Casing Liner Dia

WELL I.D. LABEL# L 11.

START CARD # 10

3159		
VIII. 0	- N. H.	
24415		

(2a) PRE-ALTERATION

Gauge Stl Plstc Wld Thrd

Amt sacks/lbs

Scrn/slot

width

Drill stem/Pump depth

5/1	4/2016		GINAL LOC		413	
	Water Qual					
Plstc Wld Thrd		Го	Descriptio	n	Amount	Units
9H H						
nt sacks/lbs						
	(10) STATI				CHILL (- ')	L Gray (a)
SEAL sacks/	SWL Date	From	To E	St Flow	SWL(psi)	+ SWL(ft)
From To Amt lbs						
Calculated						
Calculated						
Calculated						
Calculated						
	(11) WELL	LOG				
	(11) WELL	Material			From	То
_		iviateriai			TTOM	10
Gauge Stl Plstc Wld Thrd			RE	CEIVI	ED BY C	WRD
$H \times S + H$				JUN	2 4 2011	3
$H \mid S \mid S \mid H \mid H$				SA	LEM, OF	
crn/slot Slot # of Tele/						
width length slots pipe size						
			310			
					,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	Comments	/Remarks				
	None					
time is 1 hour						
Pump depth Duration (hr)						