

TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED NC
WATER WELL REPORT
MAY 25 1973
STATE OF OREGON
STATE ENGINEER
SALEM, OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
AUG 27 1973
State Well No. 6S/3W-7
State Permit No. 66912
SALEM, OREGON

(1) OWNER:
Name Lloyd RAY
Address Lone Star Rd

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
 Bored

(5) CASING INSTALLED:
Threaded Welded
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Pump test 100 gal./min. with 23 ft. drawdown after 1 hrs.
" " " " " "
" " " " " "
Temperature of water g.p.m. Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Polk Driller's well number
1/4 Section 7 T. 6S R. 3W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found ft.
Static level 23 ft. below land surface. Date 5-17-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6
Depth drilled 327 ft. Depth of completed well 327 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BASALT Broken Partly weathered	218	303	
BASALT Broken with Sappentine	303	327	
<u>Deepening</u>			

Work started 5-14 1973 Completed 5-15 1973
Date well drilling machine moved off of well 5-17 1973

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Harold R. Brandy Date 5-16, 1973
(Drilling Machine Operator)
Drilling Machine Operator's License No. 289

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Robinson Earth Well Drilling
(Person, firm or corporation) (Type or print)
Address 4510 Dallas Hwy. Salem Oregon
[Signed] George H. Robinson
(Water Well Contractor)
Contractor's License No. 13 Date 5-22, 1973