NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
FEB 11 1971
STATE ENGINEER
SALEM, OR.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

OWNER 250

State Well No. IN/16-3

State Permit No.

Copy of original Log submitted last June 10th/1970

(1) OWNER:
Name L.E. Kaseberg
Address Wasco, Oregon

(2) TYPE OF WORK (check):
New Well [X] Deepening [] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [X] Driven []
Cable [] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):
Domestic [] Industrial [] Municipal []
Irrigation [] Test Well [] Other []

CASING INSTALLED:
Threaded [] Welded [X]
8 " Diam. from 0 ft. to 21 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? [] Yes [X] No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? [] Yes [] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? [X] Yes [] No If yes, by whom? Project:Corp.
Yield: 60 gal./min. with 7 ft. drawdown after 2 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 55° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 21 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 3/4 in.
Number of sacks of cement used in well seal eleven sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [] Yes [X] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Sherman Driller's well number
¼ ¼ Section 3 T. 1N R. 16 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found fifty ft.
Static level 14 ft. below land surface. Date 5/5/70
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 8 3/4
Depth drilled fifty ft. Depth of completed well fifty ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Soil, Brown	0	2	
Gravel, Coarse	2	7	
Basalt, Brown	7	13	
Basalt, Black	13	37	
Basalt, Broken, Coarse, Gravel	37	50	

Work started May 4th 19 70 Completed May 5th 19 70
Date well drilling machine moved off of well May 5th 19 70

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Don Parry (Drilling Machine Operator) Date May 6, 1970
Drilling Machine Operator's License No. 640

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name PROJECT:Corporation (Person, firm or corporation) (Type or print)
Address 1 South Second, Walla Walla, Wn
[Signed] Dale R. Wood (Water Well Contractor)
Contractor's License No. 512 Date June 10th, 1970

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119