File Original and	LERS REPORT Do Not State Well No. 3N/17-31N/1) Fill In State Permit No. 6/49
Duplicate with the STATE ANGINEER, SALEM, OREGON	
(1) OWNER: MAR 7 1957	(10) WELL TESTS: Pump, Pipe
Name John Mathleson STATE ENGINEER	Was a pump test made? Yes \(\sigma\) No If yes, by whom? Power Co. Yield: 100 gal./min. with 43 ft. draw down after hrs.
Address Rufus, Oragon SALEM. OREGON	100
	" 150 " 91 " " "
(2) LOCATION OF WELL: App 6250	Artesian flowg.p.m.
County Sharman Owner's number, if any	Shut-in pressure
R. F. D. or Street No.	Bailer test g.p.m. with ft. drawdown
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made? Yes No
	Was electric log made of well? ☐ Yes ☐ No
	(11) WELL LOG:
	l ` ′
TYPE OF WORK (check):	Diameter of Well,
New well Deepening Reconditioning Abandon Abandon ■	
If abandonment, describe material and procedure in Item 11.	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(4) PROPOSED USE (check): (5) EQUIPMENT:	Off. to 11 ft. Soil, sand
omestic Industrial Municipal Rotary	11 " 25 " Basalt, red.
omestic [] industrial [] withhelpar []	25 " 42 " Basalt, brown, dense.
Trrigation ☐ Test Well ☐ Other ☐ Dug Well ☐	42 " 64 " Basalt, blue, dense.
(6) CASING INSTALLED: If gravel packed	64 " 105 " Basalt, grey, dense.
Threaded Welded	105 " 124 " Basalt, black, dense.
Gage Diameter from to	124 " 141 " Basalt, grey, dense.
FROM 0 ft. to 13 ft. 8 biam. Standard of Bore ft. ft.	141 " 150 " Basalt, grey, fractured.
	150 " 209 " Basalt, grey, dense.
" " pipe " " " " " " " " " " " " " " " " " " "	KOA KKK Dasare, promu
n n n n n	XXX X00 Dagait, Riel
12 23 21 23 22 27 29 29	263 " 271 " Basalt, some honeycomb, water bearing
Type and size of shoe or well ring Size of gravel:	271 " 272 " Basalt, grey dense.
Describe joint Cement	PLANT THE THEORY OF THE PROPERTY OF THE PROPER
(7) PERFORATIONS:))))
Type of perforator used	"
SIZE of perforations in., length, by in.	"
30M ft. to ft. perf per foot No. of rows	n 'n 'n
n n n n n n n n n	, "
" " " " " " " " " " " " " " " " " " " "	n n
n n n n n n	n n
	17 17
SCREENS: Give Manufacturer's Name, Model No. and Size	17 17
Give Manuacturer's Hame, Model 140, and 2	23 23
(A) CONCERNICATION.	31
(8) CONSTRUCTION: Was a surface sanitary seal provided? ☐ Yes ☐ No To what depth ft.	25
Were any strata sealed against pollution? Yes No	Ground elevation at well site feet above mean sea level.
If yes, note depth of strata	Work started Feb. 17 19 48, Completed April 22 1948
FROM ft. to ft.	Well Driller's Statement:
H H H	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
METHOD OF SEALING	true to the best of my knowledge and benefit
(9) WATER LEVELS:	NAME Dorin Wilburn (Person, firm, or corporation) (Typed or printed)
Depth at which water was first found 141 ft	Olo W Mah Campat Mha Dollar One on
Standing level before perforating ft	Address 812 E 7th Street, The Dalles, Oregon.
Standing level after perforating 59 ft	Driller's well number
Log Accepted by:	[Signed] Noun (vellum)
[Signed] Dated, 19	(Well Driller)
Owner	License No. 80 Dated March 2, 1957