WATER WELL REPORT

151

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310
within 30 days from the date of well completion. JUN 24977 write above this line)

State	Well No. 55/17 6 18	Ç
	C C	
NGS State	Permit No	

	<u> </u>
1) OWNER: WATER RESOURCES DEPT	1
Vame City of More SALEM, OREGON	County holmas - Driller's well number
Address City HAU Moro, ORE-	1) b) 1/4) E 1/4 Section 16 T. 13 R. 11 Z. W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well □ Deepening □ Reconditioning ♠ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Driven Domestic Industrial Municipal	Static level // ft. below land surface. Date 5-4-77
Cable	Artesian pressure lbs. per square inch. Date
	(12) WELL LOG: Diameter of well below casing 8'
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
8 " Diam. from 3 ft, to 33 ft. Gage 250	Depth drilled 197 ft. Depth of completed well 197 ft.
	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
	MATERIAL From To SWL
Type of perforator used Size of perforations in. by in.	
Size of periorations	RECONDITION OF SEAL
perforations from	from TEMPORARY to
perforations fromft. toft.	PERMANENT.
perforations from ft. to ft.	C CAP T// TO DE C
(7) SCREENS: Well screen installed? ☐ Yes No	PACKER INSTALLED AT
Manufacturer's Name	46'
Type Model No.	12" PIRE Drove to 321
Diam. Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	8" W/ Drive Shoe Drone
O) WELL TESTS. Drawdown is amount water level is	To 3/3'.
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	PERSONE GROUTED From
Was a pump test made? Tyes No If yes, by whom?	33' to surface
Yield: gal./min. with ft. drawdown after hrs. "Log DATE JULE " " " " " " " " " " " " " " " " " " "	
" " 1975 "	Drilled out pricker
" LOG DATE JULY	to 197'
Bailer test REFER gal./min. with ft. drawdown after hrs.	
Datter vebs 120	
Artesian flow g.p.m.	Work started 4-7 1977 Completed 5-4 1977
Perature of water Depth artesian flow encountered ft.	171
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5 -4 19/
Well seal—Material used PORTLAND CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal 1212 in.	best knowledge and belief has a first
Diameter of well bore below seal	[Signed] Hell Date 5 - B ., 19/
Number of sacks of cement used in well seal	(Drilling Machine Operator)
How was cement grout placed? PRESSURE GROUTED	Drilling Machine Operator's Lichnse No
From 0' to 33'	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
	true to the best of my knowledge and belief.
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	Name // Cay do ? Wall Jelling
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address (2360 Fly REAR Pa Beix) de
Method of sealing strata off	Issued JCR MC(.)
Was well gravel packed? ☐ Yes No Size of gravel:	[Signed] (Water Well Contractor)
	Contractor's License No. 594 Date 5-8, 197
Gravel placed from ft. to ft.	CONTRACTOR MICROSARVI SP*45656-119