NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER CALLS.

APR 13 WATER WELL REPORT

•					J	1	•
State	Well	No.	3/	15			t

STATE ENGINEER, SALEM, OREGON 97510 E ENGINETATE OF OREGON within 30 days from the date of well completion.

State Permit No. ..

(1) OWNER: U.S. Dept. of Interior Name Bureau of Land Management	(11) WELL TESTS: Drawdown is amour lowered below static		is
Address P. O. Box 37	Was a pump test made? Yes No If yes, by wh		
Prineville, Oregon		lown after	hrs.
(2) LOCATION OF WELL:	" " "	,	
	Bailer test 25 gal./min. with 3 ft. draw	down after 2	2 hrs.
County Sherman Driller's well number	Artesian flow g.p.m. Date		
NE 1/4 SE 1/4 Section 4 T. 3S R. 15E W.M.	Temperature of water Was a chemical analysi	s made? □ Ye	s (XNo
Bearing and distance from section or subdivision corner East end of campground	(12) WELL LOG: Diameter of well below		
	Depth drilled 34 ft. Depth of completed v	well 34	4 ft.
	Formation: Describe by color, character, size of mater show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each		
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Sand, gravel & boulders	0	23
Well	Packed sand & silt	23	30
If abandonment, describe material and procedure in Item 12.	Sand & boulders	30	34
(4) PROPOSED USE (check): (5) TYPE OF WELL:			
Rotary Driven		7	-
Domestic Industrial Municipal Coble		-	
Irrigation Test Well Cother Bug Dug Bored			e sa ş
(6) CASING INSTALLED: Threaded Welded 5	**************************************		
6"ID" Diam. from 0 ft. to 34 ft. Gage .250			
"Diam. from ft. to ft. Gage ft. Gage			·
"Diam. fromft. toft. Gage			
(7) PERFORATIONS: Perforated? ☐ Yes ¾ No Type of perforator used			
			
		+ +	· r
perforations fromft. toft.		+ ;	· .
perforations from	***************************************		
perforations from			
perforations from ft. to ft.		 	
		+	
(8) SCREENS: Well screen installed? ☐ Yes ঽ No			
Manufacturer's Name			
Model No.			
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Work started March 29 19 66 Completed AT	ril 6	<u> 1966</u>
	Date well drilling machine moved off of well	/r 11	19 / 1
(9) CONSTRUCTION:	(13) PUMP:		
Well seal—Material used in seal Coment & Bentonite	Manufacturer's Name		
Depth of seal18ft. Was a packer used?Sand	Type:	. H.P	***************************************
Diameter of well bore to bottom of seal			
Were any loose strata cemented off? 🗌 Yes 🏖 No 🛮 Depth	Water Well Contractor's Certification:		
Was a drive shoe used? [] Yes [X]No	This well was drilled under my jurisdiction	and this re	port is
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.		_
Gravel placed from ft. to ft.	NAME Bert Abrams		
Did any strata contain unusable water? 🔲 Yes 🏋No	(Person, firm or corporation) (7	Type or print)	_
Type of water? depth of strata	Address Route 2, Box 1114, M	adras,	Oregor
Method of sealing strata off	Duilling Wooking Openstude 7	7	
(10) WATER LEVELS:	Drilling Machine Operator's License No	.1	
Static level 15 ft. below land surface Date 4/6/66	[Signed] (Water Well Contractor)	
Artesian pressure Ibs. per square inch Date	Contractor's License No. 70 Date 4/1	1	1966
(USE ADDITIONAL SE	HEETS IF NECESSARY)		