NOTICE TO WATER WELL CONTRACTOR

The original and first copy

of this report are to be

filed with the

STATE ENGINEER, SALEM, ORE DI 97 10 within 30 days from the dath

of well completion.

WATER WELL REPORT

STATE OF OREGON

222

State Well No. 11/9w-33

(Please type or print)

(Do not write above this line)

State Permit No.

001 13 19/5		
(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:	•
Name City of Bay CityALEM, OREGON	County Tilla mook Driller's well nu	mber
Address	SW 14 SW 14 Section 33 T. IN	R. 9W W.M.
Bay City, Oregon	Bearing and distance from section or subdivision	on corner
(2) TYPE OF WORK (check):	Detaining data described in the second	<u> </u>
New Well▼ Deepening □ Reconditioning □ Abandon □	-	
If abandonment, describe material and procedure in Item 12.	(11) THAMPIN TENTET. Commission	_11
	(11) WATER LEVEL: Completed we	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1-	.7 <u>ft.</u>
Rotary Driven Domestic Industrial Municipal	Static level 17 ft. below land st	urface. Date 9/23/75
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square	e inch. Date
CASING INSTALLED: Threaded Welded X	(12) WELL LOG: Diameter of well b	
12 "Diam. from plus 2ft. to 0 ft. Gage .375	113	
12 " Diam. from 0 ft. to 26 ft. Gage	Depth drilled 60 ft. Depth of comple	eted well 465 ft.
10 "Diam from 40 ft. to $46\frac{1}{2}$ ft. Gage 250	Formation: Describe color, texture, grain size a and show thickness and nature of each stratun	
Dillin Itoli	with at least one entry for each change of format	ion. Report each change in
PERFORATIONS: Perforated? Yes XNo.	position of Static Water Level and indicate princ	cipal water-bearing strata.
Type of perforator used	MATERIAL _	From To SWL
Size of perforations in. by in.	clay gravel soil brown	0 3 12
perforations fromft. toft.	sandy gravel gray brown	3 19 12
	sand gravel water gray	19 35½ 17
perforations from	clay brown	35t 38t 17
perforations from ft. to ft.	rocky clay brown	$38\frac{1}{2}$ 42 42
(7) SCREENS: Well screen installed? ▼Yes □ No	brown weathered rock	42 60 42
Manufacturer's Name Johnson	hard rock	60 60를
Type low carbon steel Model No.		
Diam. 10 Slot size 100 Set from 20 ft. to 40 ft.	2 ¹⁷	
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	-	
10Welled below static level		
Was a pump test made? XYes \(\text{No If yes, by whom?} \) \(\text{Criller} \)		
Yield: 1200 gal./min. with 3 ft. drawdown after 24 hrs.		
n n n		
n n n		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
aperature of water Depth artesian flow encountered ft.	Work started 9/15/75 19 Complete	ed 9/2 9 /75 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9/27/75 19
Well seal—Material usedcement_grout	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my Materials used and information reported	direct supervision.
Diameter of well bore to bottom of seal	best knowledge and belief.	above are true to my
Diameter of well bore below sealin.	and a service of the	Date 9-30 , 1975
Number of sacks of cement used in well seal6Sack_Mixsacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 2/3	
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	Name Zent Drilling, Inc.	
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 7310 St. Johns Vanco	uver, Wash. 9866
Method of sealing strata off	Con alellet	-
	[Signed] (Water Well Contr	actor)
Was well gravel packed? ☐ Yes 🖫 No Size of gravel:	Contractor's License No228 Date	
Gravel placed from ft. to ft.	Contractor's License No	<i>∠4.∞≃4</i> ⊁ <i>£</i> , 13