NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED JAN 3 1977 WATER RESOURCES DEPT. SALEM, OREGON

TILL 4S / 10W 14

State Well No. 388

State Permit No.

(1) OWNER:
Name Eugene Sabine
Address P.O. Box 2684, Los Angeles Calif. 90053

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☑
6" Diam. from 1 above ft. to 32 ft. Gage .250
5" Diam. from 32 ft. to 42 ft. Gage .250
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☑ Yes ☐ No.
Type of perforator used cutting torch
Size of perforations 1/4 in. by 6 in.
30 perforations from 22 ft. to 42 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 25 gal./min. with 10 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 2 sacks
Brand name of bentonite Black Hills
Number of pounds of bentonite per 100 gallons of water 30 lbs./100 gals.
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Tillamook Driller's well number
1/4 1/4 Section 14 T. 4S R. 10W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 16 ft.
Static level 12 ft. below land surface. Date 12-22-76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing
Depth drilled 42 ft. Depth of completed well 42 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Top soil	0	3	
Brown clay	3	6	
Boulders & clay	6	16	
Boulders & sand	16	28	
gravel & sand	28	42	

Work started 12-9 1976 Completed 12-22 1976
Date well drilling machine moved off of well 12-22 1976

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Paul Dickerson (Drilling Machine Operator) Date 12-23, 1976
Drilling Machine Operator's License No. 549

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Robinson Eola Drilling (Person, firm or corporation) (Type or print)
Address 4510 Dallas-Salem Hwy
[Signed] George H. Robinson (Water Well Contractor)
Contractor's License No. 13 Date 12-24, 1976

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119