NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

STATE OF OREGON

State Well No. State Permit No. ...

(Do not write above this line)

APP 5 1978

(1) OWNER:	(10) LOCATION OF WELL:	
Name Wilson River Water District	County 7/4/9/00 Driller's well number	· ·
Address 735 WISON RIVER Loop Road	14 S=14 Section 19 T. 15 R. 9	9W W.M.
Tillamook Oregon 97141	Bearing and distance from section or subdivision corner	:
(2) TYPE OF WORK (check): U		1.7
New Well Deepening   Reconditioning   Abandon	: **	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 39	ft.
	20	2 0 70
Cable   Jetted   Domestic   Industrial   Municipal		
Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch.	Date
(5) CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well below cas	ina 12
12" Diam. from 0 ft. to 72 ft. Gage . 330	Depth drilled 72 ft. Depth of completed well	
" Diam. from		
" Diam. fromft. to	Formation: Describe color, texture, grain size and structure and show thickness and nature of each stratum and account of the structure and account of the structure.	
	with at least one entry for each change of formation. Repo position of Static Water Level and indicate principal wat	
(6) PERFORATIONS: Perforated? ☐ Yes ☑ No.		· · · · · · · · · · · · · · · · · · ·
Type of perforator used	MATERIAL From	To SWL
Size of perforations in. by in.	Topsoil	3
perforations from ft. to ft.	Lt. Brown Clay	21
perforations from ft. to ft.	Brown Sandy/ Clay 21	39
perforations from ft, to ft.	Blue Clay 39	58
(7) SCREENS: Well screen installed?   Yes   No	Black Sand & Gravel 58 Gravel 63	03
(7) SCREENS: Well screen installed? ☐ Yes ☐ No Manufacturer's Name	Snavel 63	72
Type Model No	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Diam. Slot size Set from ft. to ft.	***************************************	
Diam. Slot size Set from ft. to ft.		
	-	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made?   Yes   No If yes, by whom?		
eld: gal./min. with ft. drawdown after hrs.		
" " "		
и, и и		
an ran		
esian flow g.p.m.	2 1/2 1170 111 1	2 10 000
Temperature of water Depth artesian flow encountered ft.	Work started 3-16 1978 Completed	3-19 198
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3-19 1978
Well seal-Material used Cemen +	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct Materials used and information reported above	supervision.
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal	[Signed] Halph Jutul Date	3-30, 19 <i>78</i>
Number of sacks of cement used in well seal	(Defining Machine Operator)	254
How was cement grout placed?poured	Drilling Machine Operator's License No.	
	Water Well Contractor's Certification:	
The state of the s	This well was drilled under my jurisdiction ar	nd this report is
	true to the best of my knowledge and belief.	
Was a drive shoe used? Yes [] No Plugs Size: location ft_	Name Value	C.
Did any strata contain unusable water? ☐ Yes ₁☐ No	Of Box 111 Hillsho	ype or print)
Type of water? depth of strata	Address A.7	•
Method of sealing strata off	[Signed] Salah Luin	V -
Was well gravel packed? [ Yes [ Yoo Size of gravel:	(Water Well Contractor)	210
Gravel placed fromft. toft.	Contractor's License No.	-50,19/8