

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,  
SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

**RECEIVED**

JAN 27 1978

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

WATER RESOURCES DEPT.

TILL  
484

State Well No. 131aw-206

State Permit No.

(1) OWNER: SALEM, OREGON  
Name Wilson River Water Dist  
Address 735 Wilson River Loop Rd N.  
TILLAMOOK, ORE

(2) TYPE OF WORK (check):  
New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary  Driven   
Cable  Jetted   
Dug  Bored   
(4) PROPOSED USE (check): Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

CASING INSTALLED: Threaded  Welded   
8" Diam. from 0 ft. to 100 ft. Gage .250  
" Diam. from " ft. to " ft. Gage  
" Diam. from " ft. to " ft. Gage

PERFORATIONS: Perforated?  Yes  No.  
Type of perforator used  
Size of perforations in. by in.  
perforations from " ft. to " ft.  
perforations from " ft. to " ft.  
perforations from " ft. to " ft.

(7) SCREENS: Well screen installed?  Yes  No  
Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from " ft. to " ft.  
Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level  
Was a pump test made?  Yes  No If yes, by whom?  
Yield: gal./min. with " ft. drawdown after " hrs.  
" " " " " "  
" " " " " "  
AIR  
Bailey test 60 gal./min. with 65 ft. drawdown after 1 hrs.  
Artesian flow g.p.m.  
Temperature of water Depth artesian flow encountered " ft.

(9) CONSTRUCTION: Well seal—Material used Cement  
Well sealed from land surface to 20 ft.  
Diameter of well bore to bottom of seal 12 in.  
Diameter of well bore below seal 8 in.  
Number of sacks of cement used in well seal 5 sacks  
How was cement grout placed? PRESSURE

Was a drive shoe used?  Yes  No Plugs Size: location " ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from " ft. to " ft.

(10) LOCATION OF WELL:  
County TILLAMOOK Driller's well number  
1/4 NW 1/4 Section 20 T. 15 R. 9W W.M.  
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.  
Depth at which water was first found 26 ft.  
Static level 15 ft. below land surface. Date 1-19-78  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"  
Depth drilled 100 ft. Depth of completed well 100 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
BRN Silt + CLAY	0	12	
BRN SAND Silt	12	26	
BRN LOAM	26	36	
Cemented GRAVEL	36	41	
BRN SAND CLAY	41	57	
BRN Shale	57	82	
HARDPAN	82	100	

Work started 1-16 1978 Completed 1-19 1978  
Date well drilling machine moved off of well 1-19 1978

Drilling Machine Operator's Certification:  
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  
[Signed] Rafael Turner Date 1-21, 1978.  
(Drilling Machine Operator)  
Drilling Machine Operator's License No. 254

Water Well Contractor's Certification:  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Name TURNER DRILLING CO  
(Person, firm or corporation) (Type or print)  
Address Rt 1 Box 14 Hillsboro, ORE  
[Signed] Rafael Turner  
(Water Well Contractor)  
Contractor's License No. 247 Date 1-21, 1978