NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

within 30 days from the date of well completion.

STATE ENGINEER, SALEM, OREGON 97310

## WATER WELL REPORT

STATE OF OREGON

KECEIVED MAY 131976 Well No. Well#3

(Please type or print) WATER RESOURGES DEPTNO. 6 18/9w 2/
not write above this line) SALEM, OREGON (Do not write above this line)

(1) OWNER:	(10) LOCATION OF WELL:	
Name Fairview Water District	County Tillamook Driller's well number	
Address 403 Marof Drive	14 14 Section 21 T.1 S R. 9 W W.M.	
Tillamook, Oregon 97141	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon	-	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 142 ft.	
Rotary ☐ Driven ☐ Domestic ☐ Industrial ☐ Municipal 🛣	Static level 31 ft. below land s	urface. Date 10 - 7 - 7
Dug 🛘 Bored 🗀 Irrigation 🖨 Test Well 🗎 Other 🖂	Artesian pressure Ibs. per squar	e inch. Date
CASING INSTALLED: Threaded □ Welded ☐ 16 " Diam. from 0 ft. to 174 ft. Gage 275 ft. to 174 ft. Gage PERFORATIONS: Perforated? ▼ Yes □ No.	(12) WELL LOG: Diameter of well below casing16!!.  Depth drilled 174 ft. Depth of completed well 174 ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Type of perforator used Drive down perforator	MATERIAL	From To SWL
Size of perforations $\frac{1}{4}$ in. by $\frac{1}{1}$ in.	Top soil	0 13
288 perforations from 142 ft. to 148 ft.	Yellow clay	15 11
152 perforations from 162 ft. to 166 ft.	Blue clay	11 39
perforations fromft. toft.	Cemented grave1	39 142
(7) SCREENS: Well screen installed?   Yes X No	Loose grave1	142 148
Manufacturer's Name	Cemented grave1	148 162
Type	Loose grave1	162 166
Diam Slot size Set from ft. to ft.	Cemented grave1	166 174
Diam ft. to ft.		
Drawdown is amount water level is lowered below static level  Was a pump test made? Yes Wo If yes, by whom? by owner  Yield: gal./min. with ft. drawdown after hrs.	Application Iva.	G-7366
nimn	1. MAC 6	
	with Enter Control Minus Control Contr	
Artesian flow g.p.m.	7	
perature of water Depth artesian flow encountered ft.	Work started 5-6c+ 1973 Complete	d 20 Bet 1974
(9) CONSTRUCTION:	Date well drilling machine moved off of well	26 GET 1974
Well seal—Material used Cement  Well sealed from land surface to 45  Diameter of well bore to bottom of seal 19-1/2 in.  Diameter of well bore below seal 16  Number of sacks of cement used in well seal 41  sacks  Number of sacks of bentonite used in well seal 5  sacks  Brand name of bentonite	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.  [Signed]  (Drilling Machine Operator)  Drilling Machine Operator's License No. 235	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of waterlbs./100 gals.	This well was drilled under my jurisdic true to the best of my knowledge and beli	
Was a drive shoe used? 🗷 Yes 🔲 No Plugs Size: location ft.		
Did any strata contain unusable water? 🗌 Yes 🧏 No	Name (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed]	
Was well gravel packed?   Yes  No Size of gravel:	(Water Well Contra	etor)
Gravel placed fromft. toft.	Contractor's License No Date	, 19
/TIOP A W		