STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210) TILL 52659

2/21/2017

WELL I.D. LABEL# START CARD# ORIGINAL LOG # TILLAMOOK 52648

			rage	OI.	J
L	122270				
	1033495				
	TILLAMOOK	52648			

(1) LAND OWNER Owner Well I.D.			
First Name Last Name	(9) LOCATION OF WELL (legal description)		
Company PORT OF TILLAMOOK BAY	County TILLAMOOK Twp 1.00 S N/S Range 10.00 W E/W WM		
Address 4000 BLIMP BLVD SUITE 100	Sec 24 NW 1/4 of the SW 1/4 Tax Lot 600		
City TILLAMOOK State OR Zip 97141 (2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot		
Alteration (complete 2a & 10) X Abandonment(complete 5a)	Tax Map Number Lot Lat " or 45.46910747 DMS or DD		
(2a) PRE-ALTERATION	Long or123.86327205 DMS or DD		
Dia + From To Gauge Stl Plstc Wld Thrd	Street address of well Nearest address		
Casing:	509 GOODSPEED ROAD TILLAMOOK OREGON		
Material From To Amt sacks/lbs			
Seal:	(10) STATIC WATER LEVEL		
Rotary Air Rotary Mud Cable Auger Cable Mud	Date SWL(psi) + SWL(ft)		
Reverse Rotary X Other MIXED AND PUMPED	Existing Well / Pre-Alteration		
	Completed Well 2/16/2017 3		
(4) PROPOSED USE Domestic Irrigation Community	Flowing Artesian? Dry Hole?		
Industrial/Commericial Livestock Dewatering	WATER BEARING ZONES Depth water was first found		
Thermal Injection Other	SWL Date From To Est Flow SWL(psi) + SWL(ft)		
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)			
Depth of Completed Well ft.			
BORE HOLE SEAL sacks/			
Dia From To Material From To Amt lbs			
Calculated			
Calculated			
Calculated	(11) WELL LOG Ground Elevation		
How was seal placed: Method A B C D E	Material From To		
Other			
Backfill placed from ft. to ft. Material			
Filter pack from ft. to ft. Material Size			
Explosives used: Yes Type Amount			
(5a) ABANDONMENT USING UNHYDRATED BENTONITE			
Proposed Amount Actual Amount			
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd			
Shoe Inside Outside Other Location of shoe(s)			
Temp casing Yes			
(7) PERFORATIONS/SCREENS			
Perforations Method			
Screens Type Material Perf/ Casing/ Screen Scrn/slot Slot # of Tele/	Date Started 2/16/2017 Completed 2/16/2017		
Screen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification		
madi. Tengui.	I certify that the work I performed on the construction, deepening, alteration, or		
	abandonment of this well is in compliance with Oregon water supply well		
	construction standards. Materials used and information reported above are true to the best of my knowledge and belief.		
	License Number Date		
(8) WELL TESTS: Minimum testing time is 1 hour	Signed		
Pump Bailer Air Flowing Artesian			
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification		
	I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well		
To the analysis V Dr.	construction standards. This report is true to the best of my knowledge and belief.		
Temperature 57 °F Lab analysis Yes By Water quality concerns? Yes (describe below) TDS amount 15 ppm	1		
Water quality concerns? Yes (describe below) TDS amount 15 ppm From To Description Amount Units	License Number 1962 Date 2/21/2017		
	Signed STEVE KASER (E-filed)		
	Contact Info (optional) STEVE KASER #1962 503 881 9255		

TILL 52659

WELL I.D. LABEL# L
START CARD # 1
ORIGINAL LOG # 1

L	122270	
‡	1033495	
#	TILLAMOOK	52648

Amount Units

+ SWL(ft)

То

continuation page	2/21/2017 ORIGINAL LOG # TILLAMOOK
(2a) PRE-ALTERATION	Water Quality Concerns
Dia + From To Gauge Stl Plstc Wld Thrd	From To Description Ar
Material From To Amt sacks/lbs	
(5) PODE HOLE CONCEDUCATION	(10) STATIC WATER LEVEL
(5) BORE HOLE CONSTRUCTION BORE HOLE SEAL	SWL Date From To Est Flow SWL(ps
D: D D	sacks/ mt lbs
Calculated	
Calculated	
Calculated	
Calculated	_
FILTER PACK From To Material Size	(11) WELL LOG
	Material From
(6) CASING/LINER	
Casing Liner Dia + From To Gauge Stl Plstc W	id Thrd
	ı
	4 H- 1
	· -
(7) DEDEOD ATIONS/SCREENS	
(7) PERFORATIONS/SCREENS	
Perf/ Casing/ Screen Scrn/slot Slot # o Screen Liner Dia From To width length slot	
Trom or wrem rengm	
	Comments/Remarks
	THE FOLLOWING STEPS WERE TAKEN IN DECOMMIS
(8) WELL TESTS: Minimum testing time is 1 hour	WELL CASING WAS CUT OFF FIVE FEET ABOVE GRO

Duration (hr)

Drill stem/Pump depth

Yield gal/min

Drawdown

THE FOLLOWING STEPS WERE TAKEN IN DECOMMISSIONING THIS WELL. CASING WAS CUT OFF FIVE FEET ABOVE GROUND. A TREMME HOSE WAS INSTALLED TO THE BOTTOM OF THE WELL. A NEET CEMENT GROUT CONSISTING OF 5 GALLONS WATER PER SACK OF PORTLAND CEMENT WAS MIXED AND PUMPED INTO THE WELL. THE TREMME HOSE WAS KEPT BELOW THE LEVEL OF CONCRETE IN THE WELL AT ALL TIMES. THE MIXING AND PUMPING CONTINUED UNTIL CEMENT GROUT FLOWED OVER THE TOP OF THE CASING. THE TREMME HOSE WAS REMOVED FROM THE WELL. A TOTAL OF 30 BAGS

TILL 52659

2/21/2017

Map of Hole

STATE OF OREGON WELL LOCATION MAP

This map is supplemental to the WATER SUPPLY WELL REPORT

Oregon Water Resources Department

725 Summer St NE, Salem OR 97301 (503)986-0900



LOCATION OF WELL

Latitude: 45.4691074706 Datum: WGS84

Longitude: -123.86327204704

Township/Range/Section/Quarter-Quarter Section:

WM 1S 10W 24 NWSW

Address of Well:

509 GOODSPEED ROAD TILLAMOOK OREGON

Well Label: 122270

Printed: February 21, 2017

DISCLAIMER: This map is intended to represent the approximate location the well. It is not intended to be construed as survey accurate in any manner.

Provided by well constructor

