

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

RECEIVED STATE OF OREGON

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

APR 5 1968 (Please type or print) Do not write above this line

TILL 609

State Well No. 1/10w-2 dc

State Permit No.

STATE ENGINEER SALEM OREGON

(1) OWNER:

Name Lawrence M. Bixler Address 2465 Margery Court, Eugene, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [x] Municipal [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

8" Diam. from 0 ft. to 88 ft. Gage wall Threaded [] Welded [x]

(6) PERFORATIONS:

Perforated? [] Yes [x] No

Type of perforator used

Table with columns: Size of perforations, in. by, in., ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 12 ft. below land surface Date 3-26-68 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [x] No If yes, by whom?

Table with columns: Well, gal./min. with, ft. drawdown after, hrs. Bailer test 50 gal./min. with 60 ft. drawdown after 1 hrs.

(10) CONSTRUCTION:

Well seal—Material used Bentonite Depth of seal 12" seal at 45 ft. Diameter of well bore to bottom of seal 12" in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [] Yes [x] No Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Tillamook Driller's well number 1/4 1/4 Section 2 T. 1S R. 10W W.M.

Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 8"

Depth drilled 105 ft. Depth of completed well 105 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Top Soil 0 3 Brown Sand and gravel 3 75 Gravel and logs 75 80 Blue sand and gravel 80 105

Work started 3-26 1968 Completed 3-26-68 19

Date well drilling machine moved off of well 3-26-68 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ralph Turner Date 4-2, 1968 (Drilling Machine Operator)

Drilling Machine Operator's License No. 254

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Ralph Turner Drilling Co (Person, firm or corporation) (Type or print)

Address Rte 1 Box 141, Hillsboro, Oregon

[Signed] Ralph Turner (Water Well Contractor)

Contractor's License No. 247 Date 4-2, 1968