NOTICE TO WATER WELL CONTRACTOR.

The original and first copy of this report are to be filed with the JUL 201971

STATE OF OREGON

State Well No.	13/9W-6
----------------	---------

STATE ENGINEER, SALEM OREGONO SIDE NOTIFICE (Please type or print) within 30 days from the date EEN. OREGO(Do not write above this line)

State Permit No. ..

(1) OWNER:	(10) LOCATION OF WELL:
Name Kilchis Water District	County Tillamook Driller's well number //915-6/
Address Rt.1 Box 582	14 14 Section 6 T. 1.3 R. 9 (CU W.M.
Bay City Ore. 97107	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🛱 Deepening 🗆 Reconditioning 🗀 Abandon 🖂	1 <sub>V</sub>
If abandonment, describe material and procedure in Item 12.	(11) WADED LEVEL. Completed will
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary D Driven D	Depth at which water was first found 14 ft.
Cable  Jetted  Domestic  Industrial  Municipal	Static level 13 ft. below land surface. Date 7/27/7
Dug	Artesian pressure - lbs. per square inch. Date
CASING INSTALLED:  8 5/8 Diam. from 140 ft. to 62 ft. Gage 700  "Diam. from ft. to ft. Gage 7 Diam. from ft. Gage 7 Diam. ft. Gage 7 Diam. from ft. Gage 7 Diam. ft. G	(12) WELL LOG: Diameter of well below casing
Type of perforator used Mills	MATERIAL From To SWL
Size of perforations $3/8$ in. by 2 in.	River silt 0 14
128 perforations from 52 ft. to 61 ft.	Small gravel rusty
perforations fromft. toft.	stain 14 18
perforations fromft, toft.	Clean gravel 18 19
	Blk stilty clay 19 50
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Loose gravel 50 52
Manufacturer's Name	Gravel with grey clay   52   58
Type Model No.	Gravel with brwn clay 58 60
Diam. Slot size Set from ft. to ft.	Tight gravel with boulders
Diam. Slot size Set from ft. to ft.	and grey clay 60 70
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	###. ###.  ###.  12.  13.  14.  14.  15.  15.  15.  15.  15.  15
Was a pump test made? ☐ Yes 🗵 No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" " "	
II	
Bailer test 50 gal./min. with 5 ft. drawdown after 7 hrs.	Victor and Market and
Artesian flow g.p.m.	
rature of water Depth artesian flow encountered ft.	Work started 7/16 1971 Completed 7/21/71 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7/22/71 19
Well seal-Material used Bentonite & Clay	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator) Date 7/23., 1971.
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No69
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	Name Harry A Robinson
Did any strata contain unusable water?   Yes   No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 2214 Front St NE Salem, Ore.
Method of sealing strata off	[Signed] Harry a Robinson
Was well gravel packed? ☐ Yes K No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 22 Date 7/23/71 , 19