NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310

Type of water?

Method of sealing strata off

Gravel placed from

Was well gravel packed? [Yes [No

WATER WELL REPORT E I VED

STATE OF OREGON FEB - 8 1978

of well completion.	OVEWATER RESOURCES DEPT.),	***************************************
(4) OXIVER	CALEM, OREGON		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Wilson River Water Dist	County Tillamook Driller's well number		
Address 735 Wilson River Loops Rd	14 SE 14 Section 19 T. 15	R. 9W	W.M.
TillAmook ORE. 97141	Bearing and distance from section or subdivision	n corner '	
(2) TYPE OF WORK (check):	2 22112		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	21	ft.
Rotary Driven Domestic Industrial Municipal Cable Jetted D	Static level 12 ft. below land st	urface. Date	1-29-78
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square	inch. Date	•
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	elow casing	8"
8 " Diam. from C ft. to 70 ft. Gage . 250	Depth drilled 70 ft. Depth of comple	_	76 ft.
ft, toft. Gage			
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratur		
PERFORA MYONG	with at least one entry for each change of format		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princ	cipal water-bea	tring strata.
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Top Soil	0 3	
perforations from ft. to ft.	Lt BRN CINY	3 21	
perforations fromft. toft.	BRN SANDY Clay	21 39	
perforations from	Blue CIAY	39 58	<u> </u>
	Black Sand	58 63	
(7) SCREENS: Well screen installed? Yes No	GRAVE	63 70	
Manufacturer's Name			
Type Model No.			
Diam Slot size Set from ft. to ft.	-		
Diam. Slot size Set from ft. to ft.		<u> </u>	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	:		
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
	- to the total terms of the ter		
" " " " " " " " " " " " " " " " " " "			
All and a second a			
Saller test 300 gal./min. with 39 ft. drawdown after 1 hrs.		 	
Artesian flow g.p.m.		<u> </u>	_
perature of water Depth artesian flow encountered ft.	Work started 1-27 1978 Complete		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1-28	19 78
Well seal—Material used Cement	Drilling Machine Operator's Certification:		
Well sealed from land surface to 54 ft.	This well was constructed under my	direct sup	ervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and ballets	apove are ti	ue to my
Diameter of well bore below sealin.	[Signed] Stalph July	Date 2-6	1978
Number of sacks of cement used in well seal	(Drilling Machine Operator)	n rii	
How was cement grout placed? pressure	Drilling Machine Operator's License No.	254	
111111111111111111111111111111111111111	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft,	Tinuan Dailling C	0	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Rtl Boy IHI Hills boi	RO 9712	<u> </u>

[Signed] -

Contractor's License No. 247 Date

19.7.8