NOTICE TO WATER W The original ar of this repor-filed with

WATER WELL REPORT

STATE OF OREGON

TILL	•			-
(849)		3/10		30
State	Well No.	2/16	/ W;	~ ~
		-		1.

STATE ENGINEER, SALEM OREGON 97310 (Please type within 30 days from the date L. V. 1912 E. R.	or print) State Permit			a	
of well complited EM OFICEN (Do not write al	ove this line)				
(1) OWNER:	(10) LOCATION OF WELL:				
Name Sius/AW NATIONAL Forest.	County I AMOSK Driller's well	number		-	
Address P.O. 130x 3623	. ¼ ¼ Section 30 T. 35	R. 10	<u>(4)</u>	W.M.	
Portland, ORe	Bearing and distance from section or subdiv				
(2) TYPE OF WORK (check):	Bearing and distance from section of subdiv	ISIOII COIIIEI			
New Well Deepening □ Reconditioning □ Abandon □	÷ .				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed	well			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 20.0 ft.				
Rotary Driven Domestic Industrial Municipal D	Static level [3,0] ft. below land surface. Date 0/8/7				
Cable Dug	Artesian pressure lbs. per square inch. Date				
CASING INSTALLED: Threaded Welded Welded	(12) WELL LOG: Diameter of well	ll below casi	ng 5.	ίχ	
6. "Diam from +/ ft. to 64 ft. Gage 1280 5. "Diam from 58 ft. to 78 ft. Gage 1250	Depth drilled 78 ft. Depth of completed well 78 ft.				
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stra				
DEDECOR & MICANO	with at least one entry for each change of for position of Static Water Level and indicate p	mation. Repor	rt each	change in	
PERFORATIONS: Perforated? Yes No.	MATERIAL	From	То	swL	
Size of perforations in. by in.	Silty Sand, yellow		68	SWE	
perforations from ft. to ft.					
perforations from ft. to ft.	S'And, brown	68	78	12.0	
perforations from ft. to ft.	WAter Stratum				
(E) COPERIO					
(7) SCREENS: Well screen installed? Yes \(\square\) No					
Manufacturer's Name		\bot		<u> </u>	
Type Stainless, Steek Model No.				<u> </u>	
Diam				<u> </u>	
Diam. Slot size Set from ft. to ft.					
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		-		 	
Was a pump test made? Yes \(\text{No If yes, by whom?} \)					
was a pump test made? Me Yes Li No II yes, by whom?		+			
Yield: 30 gal./min. with 45.5 ft. drawdown after hrs.				 	
" " "	the state of the s			<u> </u>	
" " "					
Bailer test 20 gal./min. with 20 ft. drawdown after 1/2 hrs.					
Artesian flow g.p.m.					
perature of water Depth artesian flow encountered ft.	Work started Sapt 27 197/ Comp	leted Oc-	-8	197/	
(9) CONSTRUCTION:	Date well drilling machine moved off of well Oct 8 197/				
Well seal-Material used Bentonite	Drilling Machine Operator's Certification	n:			
Well sealed from land surface to 20 ft.	This well was constructed under n				
Diameter of well bore to bottom of sealin,	Materials used and information reported best knowledge and belief.	a above a	re true	e to my	
Diameter of well bore below seal	[Signed Teroy W Mulochlor	Date 10	18	10/	
Number of sacks of cement used in well sealsacks	Ørilling Machine Operator)	<i></i>	~		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No) <i>6</i> C	<i></i>		
Brand name of bentonite NATIONAL	TWO AND TWO IN COMMAND AND COMMENTS OF THE COM	<u> </u>			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		3 43. 1		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.				
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	Name L.W. Mutschler Well	Drilli	na		
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Tyr	e or pri	nt) ALLIS	
Type of water? depth of strata	Address 7555 NW. OAK Creek	< DY	Ore	900	
Method of sealing strata off	[Signed] Droll W Mulas	hos	_/		
Was well gravel packed? Yes No Size of gravel:	(Water Well Co	ntractor)	Q	7	
Gravel placed from ft. to ft.	Contractor's License No	101		, 19.//	