WATER WELL REPORT STATE OF OREGON

10 8

RECEIVED

JAN 1 9 1981

State Well N

'n	4	5	-	10	W -	74	b
υ.			• • • • • •				

WATER RESOURCES DEPT SALEM, OREGON

State Permit N	o	 	
	Appl.		-

(1) OWNER:	(10) LOCATION OF WELL:				
Name Pacific City Water District Well #3	County Tillamook Driller's well number				
Address Pacific City, Oregon	40 4 C 10 H	W.M.			
City State	Tax Lot # Lot Blk Subdivision				
(2) TYPE OF WORK (check):	Address at well location:				
New Well Deepening □ Reconditioning □ Abandon □					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.				
	Depth at which water was first found 45 ft.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 5 ft. below land surface. Date 1/10/81 Artesian pressure lbs. per square inch. Date				
Air Driven Domestic Industrial Municipal Kenary Mud Z Dug Irrigation Test Well Other					
Cable	(12) WELL LOG: Diameter of well below casing				
(5) CASING INSTALLED: Steel Plastic	Depth drilled 75 ft. Depth of completed well 75	ft.			
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.				
LINER INSTALLED:	MATERIAL From To SV	WL			
	Fine brown sand 0 50	WL			
ft. toft. Gauge	Fine gray-brown sand 50 65				
(6) PERFORATIONS:Perforated? □ Yes No	Fine gray sand w/clay 65 75				
Type of perforator used	8				
Size of perforations in. by in.					
perforations from					
perforations from ft. to ft.					
perforations from ft. to ft.					
(7) SCREENS: Well screen installed?					
Manufacturer's Name UOP JOHNSON					
Type Stainless Steel Model No. Diam. 8 ¹¹ Slot Size • 020. Set from 45. ft. to 65. ft.					
Diam. Slot Size Set from ft. to ft. On which I would be set from samount water level is lowered					
WELL TESTS: Drawdown is aniount water lever is lowered below static level					
Was a pump test made? 🛂 Yes 🗆 No If yes, by whom? AMJANNSEN					
Yield: 85 gal./min. with 35 ft. drawdown after 8 hrs.		 -			
<i>"</i> " " " " " " " " " " " " " " " " " "		 .			
Air test gal./min, with drill stem at ft. hrs.					
er test gal./min. with ft. drawdown after hrs.					
Artesian flow g.p.m.					
	Work started 1/6/81 19 Completed 1/10/81	19			
(9) CONSTRUCTION: Special standards: Yes \(\sigma \) No (X)	4 /4 0 / 04	19			
Well seal—Material used Cement	Drilling Machine Operator's Certification:				
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used				
Diameter of well bore to bottom of seal 14 in.	and information reported above are true to my best knowledge and belief.				
Diameter of well bore below sealin.	[Signed] Date 1/15/87	.			
Number of sacks of cement used in well seal 10 sacks	Drilling Machine Operator's License No. 751				
How was cement grout placed? Tremmed into annular @ 201					
back to surface	Water Well Contractor's Certification:	_			
20	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.				
Was pump installed? <u>no</u> Type <u>HP</u> Depth <u>ft.</u>	Name A. M. JANNSEN WELL DRILLING CO., INC.				
Was a drive shoe used?	(Type or print) Address 21075 SW Tualatin Valley Hwy. Aloha, Or.				
Did any strata contain unusable water? Yes No Type of Water? depth of strata	Address 41013 Sn Luaia Lin Valley nwy. Alona, C) L'e			
Type of Water? depth of strata Method of sealing strata off	[Signed] Ste TU MMMCh				
Was well gravel packed? ★ Yes □ No Size of gravel: #16 filte	(Water Well Contractor)	•			
Gravel placed from 20 ft to 75 ft	Contractor's License No. 79 Date 1/15/81 , 1	9			