NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report  The original and the original		
are to be inted with the	VIVIA ( )	DN133E-13C
SALEM OREGON 97310 ACC		
within 30 days from the date	State Permit N	0
The second secon	The state of the s	7
(1) OWNER: SALEM. CRECON	(10) LOCATION OF WELL:	
Name JERRY HAGGEWOOD	County L M2 TILLA Driller's well number	
Address MISSIAN RT	SW 4 SW4 Section 13 T. 2N R. 33 E W.M.	
PENDLETON ORE	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	3	
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.	
Rotary Driven Domestic Industrial Municipal	Static level 96 ft. below land s	
Cable	Artesian pressure lbs. per squar	
TARGETT TOTAL		
CASING INSTALLED: Threaded Welded Land Welded Land Brown ft. to Sage 250	1 1 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
"Diam from ft. to ft. Gage ft.	Depth drilled 2.3 (2) It. Depth of completed well 2.3 (3) It.	
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;	
	and show thickness and nature of each stratus with at least one entry for each change of format	tion. Report each change in
PERFORATIONS: Perforated?  Yes INO.	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	8014	0 12
perforations from ft. to ft.	BASELT BLZCH	12 29
perforations from ft. to ft.	CLATSTONE BROWN	29 55
perforations fromft. toft.	CREY Basout	55 65
(7) SCREENS: Well screen installed?   Yes No	BUSELY BLECH	95 110
Manufacturer's Name	li Black	110 160 106
Type Model No.	" Black + Rep	160 165 1006
Diam. Slot size Set from ft. to ft.	1. BROWN	165 175
Diam. Slot size Set from ft. to ft.	Black	175 120 400 G
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	" Black w/roce	220 230 600 G
Was a pump test made? I Yes I No If yes, by whom? ORILLER		
Yad: 600 gal,/min. with / 10 ft. drawdown after / hrs.		
" 120 " "		
" " " "	71 mm - 1	
	- · · · · · · · · · · · · · · · · · · ·	
Artesian flow g.p.m.  perature of water 62° Depth artesian flow encountered	3	326
	Work started 3/ 1978 Complete	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3-3 1978
Well seal-Material used PORTLEND CENENT	Drilling Machine Operator's Certification:	
Well sealed from land surface toff.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my	
Diameter of well bore to bottom of sealin.	best knowledge and belief.	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date 3-6 , 1978
Number of sacks of cement used in well seal sacks  How was cement grout placed? CRCULTY	Drilling Machine Operator's License No. 933	
The content growt placed:		
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used?   Yes Tho Plugs Size: location ft,	1	
Did any strata contain unusable water? 🔲 Yes 🗓 No	Name (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 5543 S.W. Dou Pendle Ton,	GLAS UR
Method of sealing strata off	[Signed]	
Was well gravel packed? Tyes No Size of gravel:		
Gravel placed from ft. to ft.	Contractor's License No. 544. Date	<u>3-6, 19/8</u>