NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON DEC181975 State Well No. 21/33 E-20

(Please type own TER RESQUECES DEPT. Permit No.

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Do not write above this IMALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	•	
Name Paul CIMM 140771	County UMATILLA Driller's well number 75-7/		
Address 115 NE Des Pain	Sw 4 NE 4 Section 20 T. 2N R. 33 E W.M.		
PENDLETON ORE	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	,		
	Depth at which water was first found		
Cable		urface. Date	
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure 2 1/35 lbs. per square	e inch. Date 8~5	~75
CASING INSTALLED: Threaded Welded S " Diam. from 12 ft. to 20 ft. Gage 250 ft. Gage 150 ft.	(12) WELL LOG: Diameter of well be Depth drilled 175 ft. Depth of complete Formation: Describe color, texture, grain size a	eted well /75	ft.
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,		
WED HOD A MICAIC.	with at least one entry for each change of format position of Static Water Level and indicate prin	ion. Report each cho cipal water-bearing	inge in strata.
PERFORATIONS: Perforated? Yes Yes.			
Type of perforator used	MATERIAL		swL
Size of perforations in. by in.	SOIL	0 10	
perforations from ft. to ft.	& Ravel	10 15	
perforations fromft. toft.	BASSIT BROKEN	15 20	
perforations from ft. to ft.	H BROWN		=Low 106
(7) SCREENS: Well screen installed? Yes You	47	90 160	
Manufacturer's Name	in Brown		ion 206
Type Model No.	Black	120 175	
Diam. Slot size Set from ft. to ft.	22.6		
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a nump test made? The I No If yes, by whom? DRILLED			·
Yield: 350 gal./min. with 300 ft. drawdown after / hrs.			
" " "			
	18 18 1 THE LAND CO.		
Bailer test gal./min. with ft. drawdown after hrs.	- The state of the	<u> </u>	
Artesian flow g.p.m.			
perature of water 64 Depth artesian flow encountered ft.	Work started 8 - 3 1975 Complete		19 75
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8-8	1975
Well seal—Material used PORTLOND COMPNT Well sealed from land surface to —30 ft. Diameter of well bore to bottom of seal 12 in.	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal	[Signed] Long Bund	Date 8 8	19.25
Number of sacks of cement used in well seal 25 sacks	[Signed] Date 8 8 , 1975 (Dryling Machine Operator) Drilling Machine Operator's License No. 933		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	iction and this re	port is
of waterlbs./100 gals.	true to the best of my knowledge and be	lief.	· · · .
Was a drive shoe used? Yes Plugs Size: location ft.	Name LZRRY BURD Wel	L DRILLI	NG.
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print	,
Type of water? depth of strata	Address P O Box 417 Px	action	
Method of sealing strata off	[Signed] Jony Burd	\$ 	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Cont		
Gravel placed from ft. to ft.	Contractor's License No. 574 Date	8-0	193