

RECEIVED

UMAT 1053

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

JUL 13 1965

WATER WELL REPORT

State Well No. 2N/33-28F

STATE ENGINEER, SALEM 10, OREGON

within 30 days from the date of well completion.

STATE ENGINEER STATE OF OREGON (Please type or print)

G 3184

State Permit No.

SALEM, OREGON

(1) OWNER:

Name Dale Tucker Address Holdman Rte Bendleton Ore

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? X Yes No If yes, by whom? Owner Yield: 80 gal./min. with 125 ft. drawdown after 10 hrs.

(2) LOCATION OF WELL:

County Umatilla Driller's well number 1/4 1/4 Section 28 T. 22N R. 335MM.M. Bearing and distance from section or subdivision corner

Bailer test gal./min. with ft. drawdown after hrs. Artesian flow 8 g.p.m. Date Temperature of water 55 Was a chemical analysis made? Yes No

(12) WELL LOG:

Diameter of well below casing 8 in. Depth drilled 470 ft. Depth of completed well 430 ft. Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

(3) TYPE OF WORK (check):

Well X Deepening Reconditioning Abandon If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic Industrial Municipal Irrigation X Test Well Other

(5) TYPE OF WELL:

Rotary Cable Dug Driven Jetted Bored

(6) CASING INSTALLED:

Threaded Welded 12" Diam. from 0 ft. to 1.10 ft. Gage 1/4 in.

(7) PERFORATIONS:

Perforated? Yes No Type of perforator used Size of perforations in. by in.

Table with columns MATERIAL, FROM, TO. Rows: Top soil, gravel and clay, black basalt coarse, grey basalt very fine, red and brown, grey basalt fine sand, black basalt broken, red coarse.

(8) SCREENS:

Well screen installed? Yes No Manufacturer's Name Model No. Diam. Slot size Set from ft. to ft.

artesian water first at 220 ft about 1 1/2 gal per min. second water was hit at 310, and continued to 430.

Work started April 1 1965 Completed July 1 1965 Date well drilling machine moved off of well July 2 1965

(9) CONSTRUCTION:

Well seal-Material used in seal Cement Depth of seal 100 to 110 ft. Was a packer used? no Diameter of well bore to bottom of seal 1.6 in.

(13) PUMP:

Manufacturer's Name red jacket Type: Submersible H.P. 10

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME ROY T FRENCH (Person, firm or corporation) Address 1015 N.W. Hazier Bendleton Ore Drilling Machine Operator's License No. 209 [Signed] Roy T French (Water Well Contractor) Contractor's License No. 107 Date July 12, 1965

(10) WATER LEVELS:

Static level art ft. below land surface Date July 1 65 Artesian pressure 5 lbs. per square inch Date 11/4/65