NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date , of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)



State Well No. ZN/33E - 29Cb

State	Permit	No.	***************************************

(1) OWNER:	(10) LOCATION OF WELL:		
Name DAVE UMBARGER	County UMETILLIF Driller's well num	nher	
Address S RESERVATION	11.1.1 C(1) AC 0 11		
PENDLETON OR	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):		1 corner	
New Well Deepening Reconditioning Abandon	12" Well		
If abandonment, describe material and procedure in Item 12.	(11) WARED LEWEL CO.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed we Depth at which water was first found	11. 783±.	
Refer Driven Domestic Domestic Municipal Domestic Municipal	Static level ft. below land sur		
Dug Bored Irrigation Test Well Other	Artesian pressure 5 lbs. per square		
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well be		
"Diam. from EXIS 17.6 NG ft. Gage	Diameter of well be	low casing	
	Formation: Describe color, texture, grain size an and show thickness and nature of each stratum	and aquifer penetrated	
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No.	with at least one entry for each change of formatic position of Static Water Level and indicate princi	n. Report each change in	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	BASALT BLECK -	750 783	
perforations from ft. to ft.	"11 BLOCK + BROWN-	783 790	
perforations from ft. to ft.	" Black	790 800	
perforations from ft. to ft.		800 875	
	21 (1 8	515 892	
(7) SCREENS: Well screen installed? Yes	11 11 11/55	892 903	
Manufacturer's Name	11 4 6/55	703 925	
Type	" BROWN-RED C	125 950	
Diam Slot size Set from ft. to ft.	" Black 9	150 965	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
lowered below static level			
Yield: 1585 gal./min. with 252 ft. drawdown after 7 hrs.	IN III PARK COLD EN IN THE PROPERTY OF THE PRO		
Yield: 1585 gal./min. with 252 ft. drawdown after 7 hrs.	<u> </u>		
" "	VIATER RESOURCES DEPT		
" " "	SALEM, OREGON		
er test gal./min. with ft. drawdown after hrs.	Sept 5 to face to 175 g		
Artesian flow g.p.m.			
Temperature of water 74° Depth artesian flow encountered ft.	Work started 1-2 1950 Completed	1-8 1980	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1-9 1980	
Well seal—Material used	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my d	irect supervision.	
Diameter of well bore to bottom of sealin.	Materials used and information reported abbest knowledge and belief.	ove are true to my	
Diameter of well bore below seal in.	TOUR TO MAKE BUILDING	1-9 ,080	
Number of sacks of cement used in well seal sacks	[Signed] Da	.te	
How was cement grout placed?	Drilling Machine Operator's License No	933	
200 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Water Well Contractor's Certification:		
Woodalaha	This well was drilled under my jurisdicti true to the best of my knowledge and belief	on and this report is	
Was a drive shoe used? ☐ Yes ☐ No Plugs	Name Jarry Burd Well D.	relline me	
Type of water? depth of strata	(Person, firm or corporation) Address Pender Tow	(Type or Frint)	
Method of sealing strata off	U. p. /		
Was well gravel packed? ☐ Yes LNo Size of gravel:	[Signed] (Water Well Contractor		
Charles and the control of the contr	Contractor's License No. 544 Date	1-9 1980	