NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the	II PEDOP	
WATER DESCRIPCES DEDARRATEMENT	775	ZN/33E -Z9
SALEM, OREGON 97310 within 30 days from the state of well completion. ATER RESOURCES SALEM. OREGON (Please type (Po not write a	pe or print)	
SALEM, OREGON 97310 FEB22 198 (Please type of well completion. FEB22 198 (Bo not write a	above this line) VG5 State Permit	No
SALEM OF DEPT		
-GUN	(10) LOCATION OF WELL:	
Name UHUID UMBARGER	County UMETILLA Driller's well i	number
Address SOUTH RESERVATION PENDLETON ORE 97801	NW 4NE 4 Section 29 T. 2N	R. 335 W.M.
<u> </u>	Bearing and distance from section or subdivis	sion corner
Now Well the Beautiful Branchis		
If abandonment, describe material and procedure in Item 12.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed v	vell.
Rotary the Driven D	Depth at which water was first found	60 ft.
Cable	Static level 6 // ft. below land	surface. Date 7-4-79
	Artesian pressure lbs. per squa	re inch. Date 7-4-76
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	
5 " Diam. from +2 ft. to -/9" 8" ft. Gage 2.50	Depth drilled 3/5 ft. Depth of comp	John J
"Diam. from ft. to ft. Gage ft	Formation: Describe color, texture, grain size	
"Diam. fromft. toft. Gage	and show thickness and nature of each strati	im and aquifer penetrated
(6) PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of forms position of Static Water Level and indicate pri	ation. Report each change in ncipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Soll	0 6
perforations from ft. to ft.	BROKEN BASALT	6 11
perforations from ft. to ft.	BROWN "	11 53
perforations from ft. to ft.	Red " w/55	53 60
(7) SCREENS: Well screen installed? Yes No	Black "	60 64
Manufacturer's Name	BROWN " W/ 35	64 87
Type Model No.	Blech "	100 140
Diam. Slot size Set from ft. to ft.	BROWN 1. BROKEN	140 160
Diam. Slot size Set from ft. to ft.	Black 11	160 215
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BROWN " W/ SS	215 218
Was a test made? If Yes No If yes, by whom? PRILLER	Bleck " Broken	218 225
i: 250 gal./min. with 200 ft. drawdown after / hrs.	BROWN " W/35	225 270
" " " " "		280 300
<i>n</i>	GREY "	300 315
Bailer test gal./min. with ft. drawdown after hrs.		
esian flow g.p.m.		
Temperature of water 54 Depth artesian flow encountered ft.	Work started 7-3 19 79 Complete	ed 7-4 19.79
(9) CONSTRUCTION:	Date well drilling machine moved off of well	-
Well seal—Material used PORTLEND COMENT		7-4 1979
Well sealed from land surface to	Drilling Machine Operator's Certification: This well was constructed under my	direct supervision
Diameter of well bore to bottom of seal12in.	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore below seal	ا مساسة	Data 7-4 10 79
Number of sacks of cement used in well seal sacks	(Drifting Machine Operator)	Date
How was cement grout placed? TREALE	Drilling Machine Operator's License No.	9.33
	Water Well Contractor's Certification:	
And the second s	This well was drilled under my jurisdi	ction and this report is
Was a drive shoe used? 🗗 Yes 🗌 No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? 🗌 Yes 🔼 🛪 o	Name Lerry Burn well (Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 5543 540 Dov 642	
Method of sealing strata off	[Signed] Burd	
Was well gravel packed? ☐ Yes ♠ No Size of gravel:	[Signed] (Water Well Contra	actor)
Gravel placed from ft. to ft.	Contractor's License No. 544 Date	7-4 1979
(USE ADDITIONAL SH		CDMSCSC 110