NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

VATER WELL REPORT MAR 17 1987

STATE OF OREGON

(Please type or print) SALEM. OREGON

(Do not write above this line) SALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name ()/NtoN Case	County Umatilla Driller's well number	
Address R+ 1 Box 180A	NE 14 NE 14 Section 7 T. 2 N R. 34 E W	7.M.
pendleton, OR 97801	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 72	. ##
Rotary Driven Domestic M Industrial Municipal D	Static level ft. below land surface. Date	
Cable		
	Artesian pressure O lbs. per square inch. Date 2-12	-81
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	
8 " Diam. from + 2 ft. to 32 ft. Gage 0.250	Depth drilled 80 ft. Depth of completed well 80	ft.
"Diam. from	Formation: Describe color, texture, grain size and structure of materi	ials:
"Diam. from ft. to ft. Gage ft. Gage	and show thickness and nature of each stratum and aquifer penetra	ted,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change position of Static Water Level and indicate principal water-bearing structure.	
Type of perforator used	MATERIAL From To SWI	
Size of perforations in. by in.	5011 06	
perforations fromft, toft.	5011 GROVEL + BONG 6 11	
perforations fromft. toft.	GRavel & Boulderes 11 19	
perforations fromft. toft.	GRAVEL, COURSE 19 27	
(T) C C T T T T T T T T T T T T T T T T T	Basalt Gree Hard 27 72	
(7) SCREENS: Well screen installed? Yes No	Basalt, Brown 72 80 +2	2
Manufacturer's Name	****	
Type Model No.	PECELVEN	-
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	IL CLIVED	
Diani. Set Hom It.	JUN 1 1 1981	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	WATER RESOURCES DEPT	
Was a pump test made? Yes No If yes, by whom? Same		
Yield: 150 gal./min. with 70ft. drawdown after hrs.	SALEM, OREGON	
" " " "		
n		
	· · · · · · · · · · · · · · · · · · ·	
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		 .
perature of water Depth artesian flow encountered ft.	Work started 2-/0- 19 87 Completed 2-/1- 19	81
(9) CONSTRUCTION:	Date well drilling machine moved off of well 2-12 19	81
Well seal—Material used Cenneyt	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision	on.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to best knowledge and belief.	my
Diameter of well bore below seal	[Signed] Clara W Sygnam Date 2-13- 19	81
Number of sacks of cement used in well seal	(Drilling Machine Operator)	_
How was cement grout placed? PU-771 ped	Drilling Machine Operator's License No.	
	Water Well Contractor's Certification:	٠ -
	This well was drilled under my jurisdiction and this report	ce an E is
Was a daire shape used CVV- C No. 70	true to the best of my knowledge and belief.	, 10
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Cillisummers Well Daillia	19
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)	P
Type of water? depth of strata	Address 11 T. H. 3. 13.01. 14.3.21. 217 17 010	<u> </u>
Method of sealing strata off	[Signed] Clasen W Lummun	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)	or i
Gravel placed from ft. to ft.	Contractor's License No. 5.75 Date 2-13- 19	5 1