NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

UMA TWATER WELL REPORT
STATE OF OREGON F G State Well No. SW/28/F &
(Please type or print)

(Do not write above this line) APR 16 1976 State Permit No.

STATE ENGINEER, SALEM, OREGON 97410 1175 of well completion.

of well completion. (Do not write abo	ove this line) AFR I DEPT. W	c11 #7	
1) OWNER:	(10) LOCATION OF WELL: County Umatilla Driller's well number 7		
ddress Star Route, Moses Lake, Wa. 98837	County Umatilla Driller's well number 7 SE 14 NW 14 Section 2 T. 3N R. 28E W.M.		
ddress Star Route, Moses Pake, Wa. 900 37	Bearing and distance from section or subdivision corner		
2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n corner -	
Tew Well □ Deepening ② Reconditioning □ Abandon □			
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
3) TYPE OF WELL: (4) PROPOSED USE (check):			
atour of Dairon D	Depth at which water was first found ft.		
able	Static level ft. below land s	÷	
bug ☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐	Artesian pressure lbs. per squar		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 10" to 300		
" Diam. from	Depth drilled 862 ft. Depth of completed well 862 ft.		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratur with at least one entry for each change of format		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princ		
Type of perforator used	MATERIAL	From To SWL	
lize of perforations in. by in.	Basalt hard black	792 820	
perforations from ft. to ft.	Basalt hard gray	820 840	
perforations from ft. to ft.	Basalt soft blk some clay		
perforations fromft. toft.	blue & yellow	840 857	
	Basalt hard gray	857 862	
7) SCREENS: Well screen installed? Yes No	-		
Aanufacturer's Name	Water - 840' & 820'		
Type Model No Diam Slot size Set from ft. to ft.	<u> </u>		
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	7.5 to		
Was a pump test made? Yes No If yes, by whom?			
Vield: gal./min. with ft. drawdown after hrs.			
" " " "			
" " " " " " " " " " " " " " " " " " " "			
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.	2/2	7/25 50	
perature of water Depth artesian flow encountered ft.	Work started 1/7 19 76 Complete	ed 1/17 19 76	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1/17 19 76	
Well seal—Material used	Drilling Machine Operator's Certification:	The AT THE ROY LO	
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported		
Diameter of well bore to bottom of seal in.	best knowledge and belief.	4/13 76	
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	Date, 19	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No		
Number of sacks of bentonite used in well seal sacks			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of waterlbs./100 gals. Was a drive shoe used? \(\text{Yes} \) No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? \square Yes \square No	Name Glen Maddox (Person, firm or corporation) (Type or print)		
	Address P. O. Drawer P, Moses Lake, Wa. 98837		
	Address		
Method of sealing strata off	[Signed] (Water Well Contractor)		
Was well gravel packed? Yes No Size of gravel:			
Gravel placed from ft. to ft.	Contractor's License No. 555 Date	, 194	