NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date

of well completion.

DEC 5519772 of oregon

WATER RESOURCES DEPT.

UALEM. ORECOM

UMAT (192 State Well No. 3N 28E - 1 CC

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Emert Ranches	County Um atilla Driller's well number
Address R+1BH 23-4	
Echo, Origan 97826	SW 14 SW 14 Section // T. 377, R. 28 E. W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening □ Reconditioning □ Abandon □	N. 63° & 2620' from S.W. Corner Sec 11.
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Potony ST Dulman Fi	Depth at which water was first found /2 ft.
Cable	Static level 260 ft. below land surface. Date //- 25-77
Dug 🗍 Bored 🖺 Irrigation 💆 Test Well 🗎 Other 📙	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded 5. Welded 5. Gage	(12) WELL LOG: Diameter of well below casing
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
	MATERIAL From To SWL
Size of perforations in, by in.	7 opsore 0 2
perforations fromft. toft.	Jan 2 /2
perforations from	Gravel, Cemented & Dand 12 22 W.B. Stand & Classione Gillow 22 35
	Travel 4 Claratone, Gillow 22 35 Scarce 35 72 W.B.
(7) SCREENS: Well screen installed? Yes No	Rock, black & yellow clarition 72 78
Manufacturer's Name	Bosals black. 18 118
Type Model No.	Rock light brown 118 138
Diam. Slot size Set from ft. to ft.	Basalt, black 138 167
Diam. Slot size Set from ft. to ft.	Kock brown + yellow claybon 167 183
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Rock, byour + Green clayston 183 247
Was a pump test made? 🗆 Yes 😿 No If yes, by whom?	Kock, hard brown 247 270
Viold: and Imin with at 1	Ruck Island + aren of writing 317 347.
g Its tater down date.	Basal black 342 342
	Rock black & green Claystone 379 431 W.B.
OAK.	Basalr 431 525
Sailer test //00 gal./min. with 320 ft. drawdown after hrs.	Rock black Taken Clayothre 525 589 W.B.
Artesian flow g.p.m.	Basalt 589 605
Depth artesian flow encountered ft.	Work started //- 14 19 77 Completed // - 25 19 77
(9) CONSTRUCTION:	Date well drilling machine moved off of well //- 25 19 77
Well seal—Material used Cernery	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal 13 in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Janus Truck Date 11-25 10 77
Number of sacks of cement used in well seal 15 sacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Old any strata contain unusable water? 🕱 Yes 🗌 No	Name TROY GR/FE/15 (Person, firm or corporation) (Type or print)
Type of water? Sandy depth of strata 12'	Address 900 HERMISTON AVE, HERMISTONOS
Method of sealing strata off Casing a Ument	1 My H 11 -
Vas well gravel packed? [] Yes No Size of gravel:	[Signed]
Gravel placed from ft. to ft.	Contractor's License No. 65 Date //-25 19 77