'NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

UMAT 1225 WATER WELL REPORT E VED

STATE OF OREGON

(Please type or print) APR 16 1976

State Well No. 31/281=-34/

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

UMAT 1225

(Do not write above this line) RESOURCES DEPT. G5820

(1) OWNER: Glem Meddox	(10) LOCATION OF WELL:	
Name Teel Irrigation District	County Umatilla Driller's well number #3	
Address Rte 1, Box 95B, Hermiston, Ore	NE 14 SW 14 Section 34 T. 3	r. 28E w.m.
	Bearing and distance from section or subdivisi	
(2) TYPE OF WORK (check):	Deating and distance from section of subdivini	on come
New Well □ Deepening ☑ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(44) 774 777 7 7 7 7 7 7 7 7 7 7 7 7 7 7	
	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.	
Rotary 😿 Driven 🗋 Domestic 🗌 Industrial 🗎 Municipal 🗎	Static level ft. below land surface. Date	
Dug ☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing 10" to 560	
ft. Gage ft. Gage	Depth drilled 689 ft. Depth of completed well 689 ft.	
ft. Gageft.		
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,	
	with at least one entry for each change of forma	tion. Report each change in
PERFORATIONS: Perforated?   Yes   No.	position of Static Water Level and indicate prin	cipui water-vearing strata.
ype of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Basalt hard black	634 666
perforations from ft. to ft.	Basalt soft brown	666 670
perforations from ft. to ft.	Basalt hard black	670 674
perforations from ft. to ft.	Basalt soft brown	674 676
	Basalt hard black	676 689
(7) SCREENS: Well screen installed?   Yes   No		
Manufacturer's Name	Water 666'	
Type Model No		
Diam		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ☐ No If yes, by whom?		
· · · · · · · · · · · · · · · · · · ·		
n n n n		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
erature of water Depth artesian flow encountered ft.	Work started 1/19 19 76 Complete	ed 1/26 1976
		1/26 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1910
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my	
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
Diameter of well bore below seal in.	[Signed] Stew Moon Date 4/13 , 1976	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? 🗌 Yes 📋 No Plugs Size: location ft.	Glan Maddov	
Did any strata contain unusable water?   Yes   No	Name (Person, firm or corporation)	(Type or print)
Type of water? depth of strata	AddressP. O. Drawer P. Moses	Lake, Wa. 98837
Method of sealing strata off	Mb m	
	[Signed] (Water Well Contr	ractor)
Was well gravel packed?  Yes No Size of gravel:	Contractor's License No. 555 Date	4/73 10.76
Crowd along them	L'ONTEGOTOR'S LIGORES NO. 775 13045	₩/!n 10./W