

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

UMAT
1230

WATER WELL REPORT RECEIVED

STATE OF OREGON
(Please type or print)

APR 16 1976

State Well No. 3N/28E-35

WATER RESOURCES DEPT.
SALEM, OREGON
State Permit No.

(1) OWNER:

Name Teel Irrigation
Address Rte 1, Box 95B, Hermiston, Ore

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable Driven Jetted Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Field: gal./min. with ft. drawdown after hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number 5
NW 1/4 NE 1/4 Section 35 T. 3N R. 28E W.M.

Bearing and distance from section or subdivision corner
660I S 2630' W of NE Corner of S.35, T3N, R28E

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.
Static level 400 ft. below land surface. Date 2/28/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 12" to 500' 8" to 1055'
Depth drilled 1055 ft. Depth of completed well 1055 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Basalt soft black	878	888	
Basalt hard black	888	948	
Basalt soft black	948	973	
Basalt hard blk & gray	973	1006	
Basalt soft blk & iron pyrite	1006	1008	
clay brown, yellow & blue			
Basalt hard gray	1008	1045	
Basalt soft black	1045	1055	
Water - 950' & 1008' & 1045'			

Work started 2/23 1976 Completed 2/28 1976
Date well drilling machine moved off of well 2/28 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Steve Moore Date 4/13, 1976
(Drilling Machine Operator)
Drilling Machine Operator's License No. 755

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Glen Maddox (Person, firm or corporation) (Type or print)
Address P. O. Drawer P1 Moses Lake, Wa. 98837
[Signed] Glen Maddox (Water Well Contractor)
Contractor's License No. 555 Date 4/13, 1976