NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

state engineer, salem, oregon 97310 236 within 30 days from the date of well completion.

(Please type or print)

APR 161976

State Well No. 3N/28F35 -

within 30 days from the date of well completion. (Please type (Do not write al	State Permit N WATER RESOURCES DEPT.	To	
(1) OWNER:	(10) LOCATION OF WELL:		
Name Teel Irrigation District	County Umatilla Driller's well n	umber 6	
Address Rte 1, Box 95B, Hermiston, Ore	NE ¼ SW ¼ Section 35 T. 3	r. 28E	W.M.
Address 1100 II Don //Di 1101 milli boll Old			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	ion corner	
New Well □ Deepening ☑ Reconditioning □ Abandon □	· · · · · · · · · · · · · · · · · · ·		
If abandonment, describe material and procedure in Item 12.			
	(11) WATER LEVEL: Completed w	rell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		ft.
Rotary Driven Domestic Industrial Municipal Cable Jetted D	Static level ft. below land	surface. Date	
Dug ☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐	Artesian pressure lbs. per squar	re inch. Date	<u>to 5</u> 00
CASING INSTALLED: Threaded Welded			
	(12) WELL LOG: Diameter of well	below casing	to 591
"Diam. fromft. toft. Gage	Depth drilled 591 ft. Depth of comp	leted well 591	ft.
"Diam. from	Formation: Describe color, texture, grain size		
"Diam. fromft. Gage	and show thickness and nature of each stratu with at least one entry for each change of forma		
PERFORATIONS: Perforated?	position of Static Water Level and indicate prin		
ype of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Basalt hard blk little clav	537 560	
	Basalt soft blk clay seams	560 566	
perforations from ft. to ft.	Basalt hard black	566 580	
perforations from ft. to ft.	Basalt med soft	580 587	
perforations from ft. to ft.	Basalt soft	587 591	
(7) SCREENS: Well screen installed? Yes No	Lost circ. @ 570'	1-01 -13-	
Manufacturer's Name	Water - 587'		
Type Model No	Induct - Joy		
Diam Slot size Set from ft. to ft.			
Diam			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
<i>[</i>			
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 2/9 19 76 Complete	ted 2/21	19 76
(A) CONCERNICATION	Date well drilling machine moved off of well	2/21	19 76
(9) CONSTRUCTION:		<u> </u>	
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my		ision
Well sealed from land surface to ft.	Materials used and information reported	above are true	to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.	h/12	76
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	Date 4/13	19.
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	7 55	
Number of sacks of bentonite used in well seal sacks			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	iction and this ret	ort is
of waterlbs./100 gals.	true to the best of my knowledge and be		-
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	Name Glen Maddox (Person, firm or corporation)		
Did any strata contain unusable water? Yes No			
Type of water? depth of strata	Address P. O. Drawer P. Moses	Lake, wa. 900	2/
Method of sealing strata off	[Signed] Men mac	doap	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Cont		
Gravel placed from ft. to ft.	Contractor's License No555 Date	4/13	_{19.} 76
	,		