NOTICE TO WATER WELL CONTRACTOR The original and first copy

Of this report are to be

Of this report are to be STATE ENGINEER, SALEM, OREGON 97310 AR 2 6 1975 STATE OF OREGON FEB 4 1975 State Well No. 3N/28E-36 ab

(Please type or parts) STATE ENGINEER (Please type or print) STATE ENGINEER State Permit No. SALEM, OREGON TO SALEM, OREGON of well completion. (10) LOCATION OF WELL: (1) OWNER: County Umatilla Driller's well number Name Teel Irrigation Address Route 1, Box 95B. Hermiston. NW 14 NE 14 Section 36 T. 3N R. 28E Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): 660' S 2630' W of NE Corner of S36, T3N, R28E New Well 🕅 Deepening [Reconditioning [Abandon [7] If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first_found □X Driven □ Rotary Domestic | Industrial | Municipal | ft. below land surface. Date Cable Jetted | Bored 🗌 Irrigation X Test Well | Other 40 Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded | (12) WELL LOG: Diameter of well below casing1211 16 " Diam. from +1 ft. to 92 ft. Gage •2 Depth drilled 931 ft. Depth of completed well Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, ..." Diam. from _____ ft. to _____ ft. Gage ____ with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? Yes X No. MATERIAL Type of perforator used From 4 Top soil in. by Size of perforations 4 9 Cemented gravel perforations from ft. to ft. 9 Hard clay & gravel brown perforations from ft. to ft. Cemented gravel ... perforations from Hard clay brown 32 (7) SCREENS: 84 Well screen installed? □ Yes X No. Cemented gravel & cobbles 84 Manufacturer's Name 93 Basalt _____ Model No. _____ 128 Basalt hard 93 Diam. Slot size Set from ft. to ft. 170 Basalt soft black Diam, Slot size 170 Basalt soft red 195 Basalt hard black 195 (8) WELL TESTS: Drawdown is amount water level is lowered below static level 227 Basalt soft baack Was a pump test made? The Yes I No If yes, by whom? Basalt Hard black 250 285 Basalt soft black Vield: 1200 gal./min. with 250ft. drawdown after 14 hrs. Basalt hard black 335 362 389 Basalt soft black 389 440 Basalt hard black Bailer test gal./min. with ft. drawdown after hrs. Basalt soft black 440 160 Artesian flow g.p.m. Basalt hard black 470 perature of water Depth artesian flow encountered 619 ft. 19 74 Completed Work started 10/2 Date well drilling machine moved off of well (9) CONSTRUCTION: Well seal-Material used Neat Cement **Drilling Machine Operator's Certification:** This well was constructed under my direct supervision. Well sealed from land surface to Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore to bottom of seal ... (Drilling Machine Operator)

Date 1/17 , 1975 Diameter of well bore below seal Number of sacks of cement used in well seal Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft. Glen Maddox
(Person, firm or corporation) (Type or print) Did any strata contain unusable water?

Yes

No 145 Northshore Dr., Moses Lake, Wa. Type of water? depth of strata Method of sealing strata off [Signed] Was well gravel packed? ☐ Yes ☐ No Size of gravel: Contractor's License No. 555 Date 1/17 , 19.75

Gravel placed from _____ft. to _____ft.

NOTICE TO WATER WELL CONTRACTOR CELVED. The original and first copy of this report are to be of this report are to be the report are to be of this report are to be the report are to be of this report are to be the report are to be of this report are to be the report are to be the report are the report ar

Page 2

STATE ENGINEER, SALEM, OREGON 97370 STATE OF OREGON within 30 days from the date

FEB 4 1975 ate Well No.

within 30 days from the date STATE ENGINEER (Please type or print) STATE ENGINEER (OPERATE ENGINEER) STATE ENGINEER (Do not write above this line) SALFM, OREGON OF THE OPERATE ENGINEER (Please type or print) SALFM, OREGON OF THE OPERATE ENGINEER (Please type or print) SALFM, OREGON OF THE OPERATE ENGINEER (Please type or print) SALFM, OREGON OR THE OPERATE ENGINEER (Please type or print) SALFM, OREGON OR THE OPERATE ENGINEER (Please type or print) STATE ENGINEER (Please type or print STATE ENGINEER Permit No.

SALEM, OREGON	SALEM, OREGON			
(1) OWNER:	(10) LOCATION OF WELL:			
Name	County Umatilla Driller's well n	umber	4	
Address	NW 14 NE 14 Section 36 T. 3N	R. 2	8E	W.M.
(2) TVPF OF WORK Toback	Bearing and distance from section or subdivisi	ion corne	er	
(2) TILE OF WORK (check):				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	zell		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	CII.		•
Rotary Driven Domestic Dindustrial Distriction D	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			ft.
Capital Detted	Static level ft. below land	surface.	Date	
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	re inch.	Date	
CASING INSTALLED: _Threaded □ Welded □	(12) WELL LOG: Diameter of well	-		
	Diameter of wen			
	Depth drilled ft. Depth of comp			g ft.
ft. toft. Gage	Formation: Describe color, texture, grain size	and struc	ture of n	naterials;
PADAGO	and show thickness and nature of each stratu- with at least one entry for each change of forma	tion. Rep	ort each	change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal wat	ter-beari	ng strata.
Type of perforator used	MATERIAL	From	то	SWL
Size of perforations in. by in.	Basalt soft black	475	481	
perforations from	Basalt hard black	481	545	
perforations from ft. to ft.	Basalt soft black	545	550	
perforations from ft. to ft.	Basalt hard black	550	619	
	Basalt soft black	619	626	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Basalt hard black	626	648	
Manufacturer's Name	Basalt soft brown	648	650	
Type Model No	Basalt soft black	650	657	
Diam, Slot size Set from ft. to ft.	Basalt soft brown	657	661	
Diam Slot size Set from ft. to	Basalt soft black	661	666	
(0) TITLE & MECING	Basalt soft black	666	670	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Basalt hard black	670	690	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Basalt soft black	690	700	
Yield: gal./min. with ft. drawdown after hrs.	Basalt soft black	700	707	
" " " " " " " " " " " " " " " " " " "	Basalt hard black	707	758	
	Basalt soft black	758	765	
	Basalt hard black	765	778	
Bailer test gal./min, with ft. drawdown after hrs.	Basalt soft black	778	785	,
Artesian flow g.p.m.	Basalt hard black	785	810	-
perature of water Depth artesian flow encountered ft.	Work started 19 Complete		<u> </u>	19
(0) CONCERNICENOS	Date well drilling machine moved off of well			
(9) CONSTRUCTION:				19
Well seal—Material used	Drilling Machine Operator's Certification:			
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	direct	super	vision.
Diameter of well bore to bottom of seal in.	best knowledge and belief.	above a	are true	to my
Diameter of well bore below seal in.	[Signed]	Date		.19
Number of sacks of cement used in well seal sacks	[Signed](Drilling Machine Operator)			
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.			***********
Brand name of bentonite	Western Williams Control of the Cont	***************************************	· · · · · · · · · · · · · · · · · · ·	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:			
of water lbs./100 gals.	This well was drilled under my jurisdi true to the best of my knowledge and bel	ction an	d this r	eport is
Was a drive shoe used? 🗌 Yes 🔲 No Plugs Size: location ft.				
Did any strata contain unusable water? 🗌 Yes 🗎 No	Name (Person, firm or corporation)	(Tv	pe or prin	nt)
Type of water? depth of strata	Address			
Method of sealing strata off				
	[Signed](Water Well Contr.			
Was well gravel packed? Yes No Size of gravel:				
Gravel placed from ft. to ft.	Contractor's License No Date	· · · · · · · · · · · · · · · · · · ·		., 19

NOTICE TO WATER WELL CONTRACTOR CEIVED - The original and first copy of this report are to be filed with the

MAR 2 6 1975 STATE OF OREGON FEB 4 1975 State Well No.

STATE	EN	GINEER, SALEM, OREGO	N 973(0) \	~ U IGI Q	(73)	, and (b)		10.0
	wi	thin 30 days from the date	AT 1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	MEIGIEIMPE	(Please type or print)	STATE	EX	GINEERate Permit No
-		of well completion.	SIAIE	ENGINE CE	not write above this lin	1e).	ter i	IGINEERate Permit No.
			CALEM	OPECON		SALEM	. С	DREGON

SALEM, OREGON	OALEM, UREGUIT	
(1) OWNER:	(10) LOCATION OF WELL:	l,
Name	County Umatilla Driller's well m	ımber 4
Address	NW 4 NE 4 Section 36 T. 3N	R. 28F. W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner
	7	
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	. ft.
Rotary Driven Domestic Industrial Municipal	Static level ft. below land s	
Cable	Artesian pressure lbs. per squar	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well h	pelow casing
" Diam. from ft. to ft. Gage	Depth drilled ft. Depth of compl	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a	and structure of materials:
"Diam. fromft. toft. Gage	and show thickness and nature of each stratur	n and aquifer penetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of format position of Static Water Level and indicate prin	
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Basalt soft black	810 818
·	Basalt hard black	818 844
perforations from ft. to ft.	Basalt soft black	844 850
perforations from ft. to ft.	Basalt hard black	850 856
	Basalt soft black	856 858
(7) SCREENS: Well screen installed? Yes No	Basalt hard black	858 879
Manufacturer's Name Model No	Basalt soft black	879 903
	Basalt hard black	903 912
Diam Slot size Set from ft. to ft.	Basalt soft black	912 931
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom?		
Wilder and American State of the Control of the Con	#V	
ALL DE LA COLUMN AND AND AND AND AND AND AND AND AND AN		
the state of the s		
n n n n n n n n n n n n n n n n n n n		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
erature of water Depth artesian flow encountered ft.	Work started 19 Complete	d 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	19
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my	direct supervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore below seal in.	[Signed]	Date 19
Number of sacks of cement used in well seal sacks		•
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons		-12-m 3 17 to
of water lbs./100 gals.	This well was drilled under my jurisdi true to the best of my knowledge and beli	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name	
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address	***************************************
Method of sealing strata off	[Signed]	
Was well gravel packed? Yes No Size of gravel:	[Signed](Water Well Contra	actor)
Gravel placed from ft. to ft.	Contractor's License No Date	, 19

Page 3

NOTICE TO WATER WELL CONTRACTOR

> The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Do not write abo	ove this time TER RESOURCES DEPT.	O,		***********
	SALEM, CRECON (10) LOCATION OF WELL:			
	County Umatilla Driller's well nu	ımber	#2	
e	NW 14 NE 14 Section 36 T. 3N	R. 2	8E	W.M.
	Bearing and distance from section or subdivision			
	660' S 2630' W of NE Corner o			R28E
Abandon 🗌			· · · · · · · · · · · · · · · · · · ·	
	(11) WATER LEVEL: Completed w	ell.		
E (check):	Depth at which water was first found			ft.
] Municipal 🔲	Static level ft. below land s	urface.	Date	
Other 🗆	Artesian pressure Ibs. per squar	e inch.	Date	
elded 🗆	(12) WELL LOG: Diameter of well h		12" to	
ıge	Depth drilled 1005 ft. Depth of comple			-
ıge	Formation: Describe color, texture, grain size a	and struc		
ege	and show thickness and nature of each stratur with at least one entry for each change of format			
□ No.	position of Static Water Level and indicate prin	cipal wa	ter-bearir	ig strata.
	MATERIAL	From	То	swL
	Basalt hard black & gray	931	980	
ft.	Basalt med brown & soft brown		990	
ft.	Basalt hard black	990	1005	
ft.				
□ No	987' Water			
	the contract of the contract o			
£4	1			
ft.				
r level is				
ter hrs.				
,,				
<i>-</i> "		 		
after hrs.				
_				
d ft.	Work started 3/1/ 19 76 Complete	ed .	3/5	19 76
	Date well drilling machine moved off of well		3/8	19 76
***************************************	Drilling Machine Operator's Certification: This well was constructed under my		t super	vision.
ft.	Materials used and information reported best knowledge and belief.	above	are true	to my
•	reigned!	Data	4/13	1076
sacks	[Signed] Drilling Machine Operator)	Date		., 19
sacks	Drilling Machine Operator's License No.		755	
	Water Well Contractor's Certification:			
The /100 gale	This well was drilled under my jurisd		nd this r	eport is
lbs./100 gals. eation ft.	true to the best of my knowledge and bel Name Glen Maddox	ıei.		
	Name Gren Fladdox (Person, firm or corporation)	Т)	ype or pri	nt)
	Address P. O. Drawer P. Moses La	ake.,	da98	837
	[Signed] Hen mad	lda		
	[Signed] (Water Well Control	actor)		
it.	Contractor's License No555 Date	4/13	3	, 197.6

No Filing)
(1) OWNER:
Name Teel Irrigation
Address Route 1, Box 95B, Hermiston, Ore
223
(2) TYPE OF WORK (check):
New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.
(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary ☑ Driven ☐ Domestic ☐ Industrial ☐ Municipal ☐ Dug ☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐
CASING INSTALLED: Threaded Welded
CASING INSTALLED: Threaded Welded ft. to ft. Gage
"Diam. from ft. to ft. Gage ft. Gage
" Diam. from
PERFORATIONS: Perforated? Yes No.
Size of perforations in. by in.
perforations from ft. to ft. perforations from ft. to ft.
perforations from ft. to ft.
periorations from
(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No
Diam Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.
(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☐ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
"
n n n n n n n n
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
perature of water Depth artesian flow encountered ft.
(9) CONSTRUCTION:
Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of waterlbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off

Was well gravel packed? ☐ Yes ☐ No Size of gravel: .

Gravel placed from ft. to