

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy  
of this report are to be  
filed with the

RECEIVED

WATER WELL REPORT

RECEIVED

MAY 22 1975

STATE OF OREGON

MAY 5 1975

State Well No. 3N/29E-76C

STATE ENGINEER, SALEM, OREGON  
within 30 days from the date  
of well completion.

STATE ENGINEER (Please type or print)  
SALEM, OREGON (Do not write above this line)

STATE ENGINEER  
SALEM, OREGON State Permit No.

G-7031

UMAT  
1271

(1) OWNER:

Name Chester Prior  
Address Hermiston, Oregon

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Cable  Dug   
Driven  Jetted  Bored

(4) PROPOSED USE (check):

Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

CASING INSTALLED:

16" Diam. from 0 ft. to 33 ft. Gage 250  
" Diam. from ft. to ft. Gage  
" Diam. from ft. to ft. Gage

PERFORATIONS:

Type of perforator used  
Size of perforations in. by in.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

(7) SCREENS:

Well screen installed?  Yes  No  
Manufacturer's Name Johnson  
Type Irrigators round wire Model No.  
Diam. 16 Slot size 100 Set from 23 ft. to 33 ft.  
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level  
Was a pump test made?  Yes  No If yes, by whom? Prior  
Yield: 1530 gal./min. with 5 ft. drawdown after 12 hrs.  
Bailer test gal./min. with ft. drawdown after hrs.  
Artesian flow g.p.m.  
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Neat cement  
Well sealed from land surface to 18 ft.  
Diameter of well bore to bottom of seal 26 in.  
Diameter of well bore below seal 26 in.  
Number of sacks of cement used in well seal 50 sacks  
Number of sacks of bentonite used in well seal sacks  
Brand name of bentonite  
Number of pounds of bentonite per 100 gallons  
of water lbs./100 gals.  
Was a drive shoe used?  Yes  No Plugs Size: location ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel: 1" RR  
Gravel placed from 18 ft. to 33 ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number 3  
SW 1/4 NW 1/4 Section 7 T. 3N R. 29E W.M.  
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 3 ft.  
Static level 3 ft. below land surface. Date 4/14/75  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0  
Depth drilled 33 ft. Depth of completed well 33 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	8	
Sand	8	15	
Coarse sand-gravel-sm cobbles	15	32	
Clay & gravel cemented	32	33	
Basalt	33		

Work started 4/14 1975 Completed 4/17 1975  
Date well drilling machine moved off of well 4/21 1975

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  
[Signed] *Normand Hill* Date 4/22, 1975.  
(Drilling Machine Operator) 754  
Drilling Machine Operator's License No.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Name Glen Maddox  
(Person, firm or corporation) (Type or print)  
Address 145 Northshore Dr., Moses Lake, Wa. 98837  
[Signed] *Glen Maddox*  
(Water Well Contractor)  
Contractor's License No. 555 Date 4/22, 1975