

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

UMAT
1284
NC

STATE OF OREGON WATER WELL REPORT

RECEIVED

STATE OF OREGON
(Please type or print)

DEC 11 1974

State Well No. 3N/29E-11

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

(Do not write above this line) STATE ENGINEER
SALEM, OREGON State Permit No.

(1) OWNER:

Name Circle C Farms
Address Pr 2
Echo, Oregon 97826

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Well: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used not disturbed
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number
1/4 1/4 Section 11 T. 37N. R. 29E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 435 ft.
Static level 150 ft. below land surface. Date 11/14/74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 10"
Depth drilled 285 ft. Depth of completed well 685 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Rock, brown	400	465	W.B.
Rock, black	465	540	
Rock, brown	540	563	
Rock, black	563	569	
Rock, brown	569	615	W.B.
Rock, hard, brown	615	640	W.B.
Basalt, hard	640	685	

This well is not completed so no test was made. It will be completed by Carl Bro. owners of the Circle C Farms.

Work started 11-7 1974 Completed 11-14 1974
Date well drilling machine moved off of well 11-14 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Troy Griffin Date 11/19, 1974
(Drilling Machine Operator)

Drilling Machine Operator's License No. 15

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name TROY GRIFFIN (Type or print)
(Person, firm or corporation)

Address 900 HERMISTON AVE, HERMISTON ORE

[Signed] Troy Griffin
(Water Well Contractor)

Contractor's License No. 65 Date 11-19, 1974