NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## 

(Do not write above this line) WATER RESOURCES DEPT.

	CHEM CALCON
(1) OWNER:	(10) LOCATION OF WELL:
Name Tim Day	County Matilla Driller's well number
Address East Birch Creek	SE 14 V E 14 Section 5 T. 15 R. 33 E W.M.
Pilot Rock OR 97868	
(2) TYPE QF WORK (check):	Bearing and distance from section or subdivision corner
New Well	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Driven Domestic Dindustrial Municipal Domestic Dindustrial	Static level . 33 ft. below land surface. Date 4-9-16
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded D Welded ID	(19) WELL LOC.
Threaded Welded Welded Welded To Threaded	(12) WELL LOG: Diameter of well below casing
_	Depth drilled 190 ft. Depth of completed well 190 ft.
"Diam from ft. to ft. Gage ft. to ft. Gage ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?   Yes   No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soil 0 3
	Broker Bacolt 3 39
perforations fromft. toft.	Black Resolt , 33 65
perforations fromft. toft.	Bruw 65 80
perforations fromft. toft.	Black Bosolt - Rad - Black GU 172
(7) SCREENS: Well screen installed?   Yes P No	Black Basalt 172 190
Manufacturer's Name	an of a total area was
Type Model No.	-
Diam Slot size Set from ft. to ft.	
Diam, Slot size Set from ft. to ft.	
(9) WITT INTEGER. Drawdown is amount water level is	
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes   No If yes, by whom?	The state of the s
Yield: 500 gal./min. with 157ft. drawdown after hrs.	
n n	
" " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water 2 Depth artesian flow encounteredft.	Work started 4-8 1976 Completed 4-9- 1976
berature of water Depth artesian now encountered 16.	
(9) CONSTRUCTION;	Date well drilling machine moved off of well 4-10 1976
Well seal-Material used Part And CRMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Larry Harson Date 4-9, 1976
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?   Yes No Plugs Size: locationft.	Name Law Burd Mell Dulling
Did any strata contain unusable water? 🗌 Yes 🖫 No	(Berson, firm or corporation) (Type or print)
Type of water? depth of strata	Address Po Bex 417 Pulleton OP
Method of sealing strata off	Isimodi Jems Burd
Was well gravel packed?   Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 544 Date 4-15 1926