NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON (Please type or print)

(Do not write above this line)

	/
	10/000 11/
State	Well No. 15/33E-12 bb
Diace	
State	Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name WAYNE /ATT	County Umat MA Driller's well number
Address Ston St box 4	NW 1/4 NW 1/4 Section /2 T. 15 R. 33 E W.M.
- FILOT KOCK , Oray	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	1.
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal	Static level 123 ft. below land surface. Date
Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded Threaded Welded Threaded Thre	(12) WELL LOG: Diameter of well below casing 10"
"Diam from ft. to ft. Gage ft. Gage	Depth drilled 10 ft. Depth of completed well 740 ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
(6) PERFORATIONS: Perforated? Tyes No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Blackeled Bonch 3/5 688
perforations from ft. to ft.	Black Boral & Crop Tak 698 698
perforations from ft. to ft.	Black ned Book 698 728
perforations from ft. to ft.	Black Bores Rock 728 740 H, 0
(7) SCREENS: Well screen installed? Yes 500	
(1) SCREENS: Well screen installed? Yes No	
Type Model No.	
Diam. Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED
a pump test made? Yes No If yes, by whom?	OCT 171980
Yield: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT
" " " "	SALEM, OREGON
" " "	The second secon
gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Temperature of water 66 Depth artesian flow encountered ft.	Work started 9 - 23 1980 Completed 9 - 2 6 1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well 9-26 1983
Well seal-Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief
Diameter of well bore below seal in.	[Signed] Jack How Date 9-26, 1980
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 1345
How was cement grout placed?	Diffing Machine Operator & Election 140
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the feest of my knowledge and belief.
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Lt 1 Beixy PloThock Oc
Method of sealing strata off	Land Stand
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 739 Date 9-26 , 192