

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED MAR 16 1971

STATE OF OREGON (Please type or print)

RECEIVED MAR 25 1971

State Well No. 3N/30-7

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

STATE ENGINEER SALEM, OREGON

(Do not write above this line)

STATE ENGINEER

State Permit No.

(1) OWNER:

Name Vernon - Juan Cook Address P.O. Echo, Oregon 97826

UMAT 1345

(10) LOCATION OF WELL:

County Umatilla Driller's well number 1/4 1/4 Section 7 T. 37N. R. 30E. W.M. Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check):

New Well [] Deepening [] Reconditioning [x] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

CASING INSTALLED:

None" Diam. from ft. to ft. Gage " Diam. from ft. to ft. Gage " Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? [] Yes [] No.

Type of perforator used Size of perforations in. by in. perforations from ft. to ft. perforations from ft. to ft. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [] No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " " "

" " " " "

air Bailer test 660 gal./min. with 32 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal-Material used Not disturbed

Well sealed from land surface to ft.

Diameter of well bore to bottom of seal in.

Diameter of well bore below seal in.

Number of sacks of cement used in well seal sacks

Number of sacks of bentonite used in well seal sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons

of water lbs./100 gals.

Was a drive shoe used? [] Yes [] No Plugs Size: location ft.

Did any strata contain unusable water? [] Yes [] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [] Yes [] No Size of gravel:

Gravel placed from ft. to ft.

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft. Static level 8 ft. below land surface. Date 2-24-71/ Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled ft. Depth of completed well ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Handwritten entry: Enlarged and straightened hole to 13" from 66' to 347'

Work started 2-17 1971 Completed 2-24 1971

Date well drilling machine moved off of well 2-24 1971

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Troy Griffin Date 3/1, 1971 (Drilling Machine Operator)

Drilling Machine Operator's License No. 15

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name TROY GRIFFIN (Person, firm or corporation) (Type or print)

Address 925 HERMISTON AVE. HERMISTON ORE.

[Signed] Troy Griffin (Water Well Contractor)

Contractor's License No. 65 Date 3/1, 1971