NOTICE TO WATER WELL CONTRACTOR
The original and first copy

of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

UMA TWATER WELL REPORT GE VE 100 STATE OF OREGON NOV 1 1972 state Well No. 3N

(Please type or print) ATE ENGINE TE Permit No.

(Do not write above this line) LEM. OREGON

| (1) OWNER:   | (10) LOCATION OF WELL:   |                         |
|--|--|-------------------------|
| Name PATRICIA S. REW, ESTATE, ROHALDREW, ET.   |  |                         |
| Address 1042 N.W. SKYLINE DE.  | 14 14 Section 19 T. 3N R. 30 E.W.M.  |                         |
| PENDLETOH, ORE. 97801  | Bearing and distance from section or subdivision corner  |                         |
| (2) TYPE OF WORK (check):  | 4  |                         |
| New Well ★ Deepening □ Reconditioning □ Abandon □  |  |                         |
| If abandonment, describe material and procedure in Item 12.  | (11) WATER LEVEL: Completed well.  |                         |
| (3) TYPE OF WELL: (4) PROPOSED USE (check):  | Depth at which water was first found 392 ft.   |                         |
| Rotary Driven Domestic Maintenant Municipal Domestic Maintenant Municipal Domestic Maintenant Domestic Description | Static level 3/5 ft. below land s  | urface. Date 10-31-72   |
| Dug   Bored   Irrigation   Test Well   OFFICK X  | Artesian pressure lbs. per squar   |                         |
| CASING INSTALLED: Threaded ☐ Welded ☐  ———————————————————————————————————   | (12) WELL LOG: Diameter of well be Depth drilled 47.5 ft. Depth of complete  | eted well 475 ft.       |
| PERFORATIONS: Perforated?  Yes  No.  | Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. |                         |
| Type of perforator used  | MATERIAL   | From To SWL             |
| Size of perforations in. by in.  | Topsoil  | 0 7                     |
| perforations from ft. to ft.   | Rtck, blown  | 7 39                    |
| perforations from ft. to ft.   | Basalf   | 39 73                   |
| perforations from ft. to ft.   | - Kock, Light brown  | 73 87                   |
| (7) SCREENS: Well screen installed?   Yes The No.  | THE RICK, HILLE  | 87,134                  |
| Manufacturer's Name  | Rock brown   | 134 139                 |
| Type Model No.   | Basalt Rock Alack  | 139 153                 |
| Diam Slot size Set from ft. to ft.   | Rock soft brown  | 214 230                 |
| Diam. Slot size Set from ft. to ft.  | Rock black   | 230 255                 |
| (8) WELL TESTS: Drawdown is amount water level is  | Basalt, hard   | 255 344                 |
| lowered below static level   | Bascle, gray   | 344 392                 |
| Was a pump test made?   Yes  No If yes, by whom?   | - Rock, foround  | 392 396 W.B.            |
| Yield: gal./min. with ft, drawdown after hrs.  | Basalty gray   | 396 423                 |
| " "  | Rock, hard, Jught brown  | 423 430                 |
| " " " " " " " " " " " " " " " " " " "  | Ruck red   | 430 470<br>470 475 W.B. |
| Batter test /00 gal./min. with /35 ft. drawdown after / hrs.   | - Coc, seco  | 410 413 W.D.            |
| Artesian flow g.p.m.   |  |                         |
| erature of water Depth artesian flow encountered ft.   | Work started /6-/8 19 72 Complete  | d 10.30 1972            |
| (9) CONSTRUCTION:  | Date well drilling machine moved off of well   | 16-3, 1972              |
| Well seal—Material used Levnent  | Drilling Machine Operator's Certification:   |                         |
| Well sealed from land surface to 24 ft.  | This well was constructed under my direct supervision  |                         |
| Diameter of well bore to bottom of sealin.   | Materials used and information reported above are true to my best knowledge and belief   |                         |
| Diameter of well bore below seal   |  | Date 10-30, 1972        |
| Number of sacks of cement used in well sealsacks   | (Drilling MacMine Operator)  |                         |
| Number of sacks of bentonite used in well sealsacks  | Drilling Machine Operator's License No   | 665                     |
| Brand name of bentonite  | Water Well Contractor's Certification:   |                         |
| Number of pounds of bentonite per 100 gallons  | This well was drilled under my jurisdiction and this report is   |                         |
| of waterlbs./100 gals.  Was a drive shoe used?   Yes □ No Plugs Size: location ft.                                 | true to the best of my knowledge and belief.   |                         |
| Did any strata contain unusable water?  Yes V No   | Name TROY GIR / FF/N (Type or print)   |                         |
| Type of water? depth of strata   | Address 900 HERMISTON AVE,   |                         |
| Method of sealing strata off   |  | 1/ -                    |
| Was well gravel packed? ☐ Yes TNo Size of gravel:  | [Signed] [ Water Well control  | (ctor)                  |
| Gravel placed fromft. toft.  | Contractor's License No  |                         |
| (USE ADDITIONAL SH   |  | 19.72                   |
| (USE ADDITIONAL SH   | PERS IF NECESSARY)   | CD#ARORA ***            |