

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

UMAT 13le6

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

NOV 16 1976

State Well No. 3N/30E-23dd

State Permit No.

(1) OWNER:

Name Morris Temple
Address 1215 N. W. Carden
Pendleton, Oregon

(2) TYPE OF WORK (check):

New Well [ ] Deepening [X] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Driven [ ]
Cable [ ] Jetted [ ]
Dug [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ]
Irrigation [X] Test Well [ ] Other [ ]

CASING INSTALLED: Not Applicable
Threaded [ ] Welded [ ]

" Diam. from ... ft. to ... ft. Gage ...
" Diam. from ... ft. to ... ft. Gage ...
" Diam. from ... ft. to ... ft. Gage ...

PERFORATIONS: Not Applicable
Perforated? [ ] Yes [ ] No.

Type of perforator used
Size of perforations in. by in.
perforations from ... ft. to ... ft.
perforations from ... ft. to ... ft.
perforations from ... ft. to ... ft.

(7) SCREENS: Not Applicable
Well screen installed? [ ] Yes [ ] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ... ft. to ... ft.
Diam. Slot size Set from ... ft. to ... ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? [X] Yes [ ] No If yes, by whom? Farnore
Flow: 810 gal./min. with 19 ft. drawdown after 4 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Not Applicable

Well seal—Material used
Well sealed from land surface to ... ft.
Diameter of well bore to bottom of seal ... in.
Diameter of well bore below seal ... in.
Number of sacks of cement used in well seal ... sacks
Number of sacks of bentonite used in well seal ... sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water ... lbs./100 gals.
Was a drive shoe used? [ ] Yes [ ] No Plugs ... Size: location ... ft.
Did any strata contain unusable water? [ ] Yes [ ] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [ ] No Size of gravel:
Gravel placed from ... ft. to ... ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number
SE 1/4 SE 1/4 Section 23 T. 3N R. 30 E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 580 ft.
Static level 336 ft. below land surface. Date 7-12-76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: 10" cased to 320'; open 9 7/8 to 398
Diameter of well below casing 8" to 5 3/4"
Depth drilled 593 ft. Depth of completed well 593 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Basalt, Sand Stone, and other geological layers with depth ranges.

Work started July 7, 1976 Completed Oct. 15, 1976
Date well drilling machine moved off of well Oct. 15, 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Larry Burd Date 10-18, 1976
(Drilling Machine Operator)

Drilling Machine Operator's License No. 933

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Larry Burd Well Drilling
(Person, firm or corporation) (Type or print)

Address 5543 S.W. Douglas Dr., Pendleton, OR.

[Signed] Larry Burd
(Water Well Contractor)

Contractor's License No. 544 Date Oct. 18, 1976