NOTICE FO WATER WELL CONTRACTOR.

The original and first copy of this report are to ENGINEER Well No. 3N 33-24 STATE ENGINEER, SALEM, OREGON 97310 within 30 days within 30 days from the date TE ENGINES of well completions TATE NOV 2 6 900 ALLEM. OREGONATE PROMPA T CHEGOCATION OF WELL: SOGTATE E Name Sail or Water Coners Driller's well number SE 1/4 Section 34 T. 3N Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening Reconditioning [ Abandon [ If abandonment, describe material and procedure in Item 12. (3) TYPE OF WELL: (4) PROPOSED USE (check): (12) WELL LOG: Diameter of well below casing ..... Rotary ケン Domestic Industrial Municipal ft. Depth of completed well Depth drilled Jetted | Irrigation [7] Test Well □ Other Bored [ Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, (5) CASING INSTALLED: Threaded | Welded | with at least one entry for each change of formation. Report each change 12 " Diam, from 0 ft. to 50 ft. Gage 1375 in position of Static Water Level as drilling proceeds. Note drilling rates. " Diam. from \_\_\_\_\_ ft. to \_\_\_\_ ft. Gage .... MATERIAL " Diam. from \_\_\_\_\_ft. to \_\_\_\_\_ft, Gage TOPSOIL BROWN CONFLOMERATE (6) PERFORATIONS: Perforated? Yes No. BOULDERS MEDIUM Type of perforator used BROKEN BREY BASALT in, by Size of perforations 21 40 DECOMPOSED ROCK perforations from ...... ft. to ..... ft. GRAY BASALT perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. RED HONEYCOMBY WHILE REMONTH 58 perforations from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. GRAY BASALT perforations from ...... ft. to ..... RED HONEYPOHR & WILTE BENDON ft. to ...... ft. GRAY RASALT RED HONEYCONE & WHITE BENTONIN (7) SCREENS: Well screen installed? Yes ZNO RED + BLASK HOWE KOMB + GOFFWERD Manufacturer's Name 145 RED HONEYCONB 151 Diam. Slot size Set from ft. to 152 BROKEN BROWN BASALT Diam. Slot size ...... Set from ..... ft. to .... BROKEN GREY BASALT 161 (8) WATER LEVEL: Completed well. 170 GRAY BASALT REDIBLAY HONEYOUR + GREEN BENDONITE 190 20 3 ft. below land surface Date 9-9-6 c level BROKEN GREY BASALT 203 lbs. per square inch Date Artesian pressure GREY BASALT Drawdown is amount water level is lowered below static level (9) WELL TESTS: BLACK HONEYCOMB & GREEN BENTONITE GREY BASIET a pump test made? Wes \[ \] No If yes, by whom? Work started &gal./min. with 240 ft. drawdown after 94 Date well drilling machine moved off of well Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best Bailer test gal./min. with ft. drawdown after knowledge and belief. Artesian flow g.p.m. Date Oresta 1 Ball Date 14 1969 Temperature of water 57 Was a chemical analysis made? | Yes | No (10) CONSTRUCTION: Drilling Machine Operator's License No. Well seal-Material used CEMENT & CALCIVACHLORIDE Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is Diameter of well bore to bottom of seal \_\_\_\_\_\_\_in. true to the best of my knowledge and belief. Were any loose strata cemented off? 

Yes No Depth ..... Was a drive shoe used? 🔲 Yes 🏻 🏚 No Did any strata contain unusable water? 

Yes 

No depth of strata Type of water? Method of sealing strata off [Signed] . Was well gravel packed? ☐ Yes ☐ No Size of gravel: ..... Contractor's License No. 139 Date/011, 196 Gravel placed from ...... ft. to ..... ft.

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the NOV 10 19WATER WELL REPORT

NOV 10 19WATER WELL REPORT

NOV 10 19WATER WELL REPORT

OREGON

STATE ENGINEER, SALEM, OREGON 97310-TE ENGINEER type or print) within 30 days from the dates TALEM. OREGON not write above this line) of well completion.

SALEM. OREGON 97310-TE ENGINEER type or print)

OREGON 100 not write above this line)

Part 2-

State	Well	No.	

State Permit No.

(1) OWNER: PAGE 2 OF 2 PAGES	(11) LOCATION OF WELL:	(11) LOCATION OF WELL:			
Name	County (MATILLA Driller's well nu	ımber			
Address					
	Bearing and distance from section or subdivision	n corner			
(2) TYPE OF WORK (check):					
New Well Deepening Reconditioning Abandon					
If abandonment, describe material and procedure in Item 12.					
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(14) WELL LOW: Diameter of well b	oelow casi	ing	2"	
Rotary Driven Domestic Industrial Municipal	Depth drilled ft. Depth of comple	eted well	40	O ft.	
Bored   Irrigation   Test Well   Other	Formation: Describe color, texture, grain size	and struc	ture of m	aterials;	
(5) CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratu	m and ac	quifer per	netrated,	
"Diam. fromft, toft, Gage 3 7	with at least one entry for each change of form in position of Static Water Level as drilling pro				
" Diam, from ft. to ft. Gage	MATERIAL	From	То	SWL	
" Diam, from ft. to ft. Gage	BLACK HOWEYCOME & PROFILE SENTONITE	745	752		
(6) PERFORATIONS: Perforated?   Yes   No.	BLACK HOURY COME	252	256		
· · · · · · · · · · · · · · · · · · ·	GREY BASALT	756	267		
Type of perforator used	BROWN HONEYCOMB (MAIN SHITER)	2/07	272		
Size of perforations in. by in.	- BACK HONEY COHE & GYEON RESOUNTE	222	281		
perforations from ft. to	H. GREY BASALT	281	286		
perforations fromtt. to	tt. BROKEN GREY BASALT	286	292		
perforations from ft. to ft. to	et. GREY RASAIT	292	305		
		305	308		
perforations from ft. to	tt. GREY BASALT	308	318		
(7) SCREENS: Well screen installed?   Yes No	RED BLAK HONE KEAR (WATER)	3/8	327		
Manufacturer's Name	GREY BASALT	327	339		
Type Model No.	BLACK HOMEYCOME & GREEN BEAUDH IT	339	345		
Diam, Slot size Set from ft. to	" DROKEN GREY KAKALI	3/5	349		
Diam Slot size Set from ft. to	# GREY BALL	349	37/		
	- BROKEN GREY BASAL	37/	387	07	
WATER LEVEL: Completed well.	GREY RASACT	387	400	97	
tc level ft. below land surface Date					
Artesian pressure lbs. per square inch Date					
(9) WELL TESTS: Drawdown is amount water level is					
lowered below static level	173	q			
a pump test made? ☐ Yes ☐ No If yes, by whom?    Solid: 5 5 gal./min. with 248 ft. drawdown after 2 4 1	Work started 8-// 1969 Complet	ed. 1 0	9	196	
	Date well drilling machine moved off of well	0-1	1	196	
" " "		7			
	Drilling Machine Operator's Certification: This well was constructed under my displayed	irect sur	ervision	Mate	
Bailer test gal./min. with ft. drawdown after i	rials used and information reported above	ve are t	rue to r	ny bes	
Artesian flow g.p.m. Date .	knowledge and belief.	9			
Temperature of water Was a chemical analysis made? ☐ Yes ☐	No [Signed]	Date	-14	., 1962	
(10) CONSTRUCTION.	(Drilling Machine Operator)	, /**>	וייע	•	
(10) CONSTRUCTION: Penns	Drilling Machine Operator's License No.	ka.k	<u> </u>		
Well seal—Material used 50	ft. Water Well Contractor's Certification:				
Depth of seal	This well was drilled under my jurisd	iction er	nd this r	enort i	
	true to the best of my knowledge and beli	ef.	~~ with 1	CPOI I	
Were any loose strata cemented off?  Yes No Depth	NAME SUDD WIDE	V15	<u> </u>		
Was a drive shoe used? Yes No	(Person, firm or corporation)	(Тур 1	e or print)	_	
Did any strata contain unusable water?   Yes No	Address Ol L Bot 6	L 2%	2 <del>. I -</del>	- 2)	
Type of water? depth of strata	$-1$ $\mathcal{M}$ $0.0$ $\cdots$	$\mathcal{Q}$	T. (		
Method of sealing strata off	[Signed] (Jacobs	20	grang		
Was well gravel packed?  Yes No Size of gravel:		. /		<i>,</i>	
Gravel placed from ft. to ft.	Contractor's License No. 2 2 Date	2 L.S.		ر کے 19	