NOTICE TO WATER WELL CONTRACTOR The original and first copy of this top at are to be filed with the	L REPORT UMAT	
WATER RESOURCES DEPARTMENT OCT 101977 STATE OF	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	HE-699
SALEM, OREGON 97310 (Please type		
within 30 days from the VIETER RESOURCES Description.	state Permit No	
SALEM. OREGON	51,77	
(1) OWNER:	(10) LOCATION OF WELL:	
Name GILBERT BOYER, DR,	County Timatilla Driller's well number 062-77	
Address Ry 4/ Box 443	NEW NEW Section & T. 3 N. R. 34 E. W.M.	
PENDLETON, OKE,	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	- ft.
Rotary Driven Domestic Industrial Municipal	Static level 90 ft. below land surface. Da	a land
Cable Jetted Irrigation Test Well Other	Artesian pressure An and lbs. per square inch. Da	
	Artesian pressure No NE ins. per square men. Da	
CASING INSTALLED: Threaded Welded (12) WELL LOG: Diameter of well below casing		8 "
8 " Diam. from 0 tt. to 20 ft. Gage , 250	Depth drilled 5/5 ft. Depth of completed well 5/5 ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;	
	and show thickness and nature of each stratum and aqu	lifer penetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report position of Static Water Level and indicate principal water	r-bearing strata.
Type of perforator used	MATERIAL From	To SWL
Size of perforations in. by in.	3016	14
perforations from ft. to ft.		32
perforations from ft. to ft.	BROWN BASALT 32	21/2
perforations from ft. to ft.	0	59
	HARO GREV " 59	74
(7) SCREENS: Well screen installed? Yes No	SOFT BROKEN " 77 9	71
Manufacturer's Name		104 water
Type Model No		50
Diam. Slot size Set from ft. to ft.	Soft BEOWN WISORDSTONE 150 K	57
Diam. Slot size Set from ft. to ft.	GREY 11 1572	49 when
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	GREY " 23/2	47 miles
Was a pump test made? ☐ Yes ☑ No If yes, by whom?	Spanish is lightly and	462 mata
	(4Rev " 462)	541
	MED. HARD GREY 11 50/ 1	575
SI, 100 SIIII MIK OIII		
TH " H "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
Depth artesian flow encountered ft.	Work started 8-3/ 1977Completed 9-	3 19 77
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4 19 17
Well seal-Material used WEAT CEMENT	Drilling Machine Operator's Certification:	
Well sealed from land surface to 30 tt.	This well was constructed under my direct supervision.	
Diameter of well bore to bottom of sealin.	Materials used and information reported above ar best knowledge and belief	e true to my
Diameter of well bore below sealin.	[Signed] Challale Date 9	-4 1077
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	6
How was cement grout placed?	Drilling Machine Operator's License No.	
1 Comment of the Comm	Water Well Contractor's Cartification	
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name WALLACE FUELL URLY	
Did any strata contain unusable water? Yes No	Toulleon De	e or print)
Type of water? depth of strata	Address	
thod of sealing strata off [Signed]		
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)	d som
Gravel placed from ft. to ft.	Contractor's License No. 2 Date	19.7