NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT/
WATER RESOURCES DEPARTMENT STATE OF OREGON
SALEM, OREGON 97310
within 30 days from the date
of well completion.

or print)
ne date JUL 301979
(Please type or print)
n. (Do not write above this line)

WATER RESOURCES DEPT!

)	State	Well	No.	18/34E	-7bc)

State	Permit	No.	*****
5.7	-		

WAITH NEOCONOLO DELL.	
(1) OWNER: SALFM OPEGON	(10) LOCATION OF WELL:
Name Anderson Land & Livestock	County Umatilla Driller's well number
Address Pilot Rock, Oregon 97868	SWW 1/4 NW 1/4 Section & T. 1S R. 34E W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	dendring the section of subdivision corner
New Well ∰ Deepening ☐ Reconditioning ☐ Abandon ☐	9
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	
Rotary Driven D Domestic W Industrial D Municipal D	
Cable	
The state of the s	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded Welded 8 " Diam from +2 ft to 18 ft Gage .250 ft Gage	(12) WELL LOG: Diameter of well below casing 8 Depth drilled 145 ft. Depth of completed well 145 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soil 0 6
perforations from ft. to ft.	Gravel 6 12
perforations from	Black Basalt 12 45
perforations from ft. to ft.	Brown Basalt 45 58
(7) SCREENS: Well screen installed? \(\sigma\) Ver \(\sigma\) No	Black Basalt 58 63
West Bereeft Missaired! rea	Brown Porous Basalt 63 83 27
Manufacturer's Name	Red & Brown Basalt 83 100 27
Diam. Slot size Set from ft. to ft.	Black Basalt 100 129
Diam. Slot size Set from ft. to ft.	Brown Porous Basalt 129 145 27
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom?	
Yield: 400 gal./min. with 88 ft. drawdown after 1 hrs.	4.5
" "	A
П Н Н	
Bailer test gal./min. with ft. drawdown after hrs.	100
Artesian flow g.p.m.	
perature of water 56 Depth artesian flow encounteredft.	Work started 7-16 19 79Completed 7-18 1979
(9) CONSTRUCTION:	
Well seal—Material used Portland Cement Well sealed from land surface to 18	Drilling Machine Operator's Certification:
Tell bedied from faire surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal12in	best knowledge and belief
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator) Date 7-18, 19.79
Number of sacks of cement used in well seal sacks Sow was cement grout placed?	Drilling Machine Operator's License No. 1345
The second secon	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Vas a drive shoe used? ▼Yes □ No Plugs Size: locationft.	true to the hest of my knowledge and heliof
Old any strata contain unusable water? Yes No	Name Ladd HonnWell Drilling (Person, firm or corporation) (Type or print)
ype of water? depth of strata	Address Rt Box 14 Pilot Rock Ore. 97868
Method of sealing strata off	
Vas well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)
ravel placed from ft. to ft.	Contractor's License No. 739 Date 7-18 1979
ATOM AND	10.(/