NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date

JUL 301979 (Please type or print) of well completion WATER RESOURCES DEPTrite above this line)

State Permit No. ...

CALL N. LIEBURY	
(1) OWNER:	(10) LOCATION OF WELL:
Name Anderson Land & Livestock	County Umatilla Driller's well number
Address Pilot Rock, Oregon 97868	SW % NE % Section 18 T. 1S R. 34E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well 2 Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 98 ft.
Rotary Driven Domestic M Industrial Municipal Domestic M Industrial Municipal Domestic M Industrial Domestic M Industrial Domestic M Industrial Domestic Dom	Static level 36 ft. below land surface. Date
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(10) TYPE T T O C
8 "Diam. from +2 ft. to 18 ft. Gage . 250	(12) WELL LOG: Diameter of well below casing
"Diam. fromft. toft. Gage	Depth drilled 153 ft. Depth of completed well 153 ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated?   Ves   No.	with at least one entry for each change of formation, Report each change in
Terrorated: Tes Og 170.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soil 0 6
perforations fromft. toft.	Gravel 6 8 8 Black Basalt 8 25
perforations fromft. toft.	Black Basalt 8 25 Brown Basalt 25 54
perforations fromft. toft.	Black Basalt 54 65
(7) SCREENS: Well screen installed?   Yes No	Brown Basalt 65 70
Manufacturer's Name	Black Basalt 70 98
Type Model No.	Porous Brown &Black Basal t998 113 36
Diam Slot size Set from ft. to ft.	Black Basalt 113 118
Diam. Slot size Set from ft. to ft.	Porous Black Basalt 118 123 36
(8) WELL TESTS: Drawdown is amount water level is	Black Basalt 123 130
Air Tested lowered below static level	Porous Black Basalt 130 149 36
Was a pump test made?  Yes No If yes, by whom?	
Yield: 325 gal./min. with 82 ft. drawdown after 1 hrs.	=
" " " " " " " " " " " " " " " " " " "	
<i>"</i> " " " " " " " " " " " " " " " " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
nperature of water 56 Depth artesian flow encountered ft.	Work started 7-18 19 79 Completed 7-19 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7-19 19 79
Deset I are a Company	
Well seal—Material used FORTLAND Cement  Well sealed from land surface to 18	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal 12 in.	Materials used and information reported above are true to my
Diameter of well bore below seal	best knowledge and belief.
Number of sacks of cement used in well seal 10 sacks	[Signed] Date 7-26, 19 79
How was cement grout placed? <u>pumped</u>	Drilling Machine Operator's License No. 1345
The second secon	
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?   Yes No Plugs Size: location ft.	Name Ladd Horn Well Drilling
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Rt.1 Box 14 Pilot Rock. Ore 97868
Method of sealing strata off	[Signed] Todd How
Was well gravel packed?   Yes   No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 739 Date 7-26