NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTME SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL RECEIVED

STATE OF OREGON (Please type or print) MAR 25 1977 (Do not write above watter) RESOURCES DEPT.

357 35 ad State Well No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Leonard P. Hill	County Umatiela Driller's well number
Address Rt. 1 Boy 214	SE 1/4 ME1/4 Section 35 T. 371. R. 35E. W.M.
Address Rt. 1 Boy 214 Adams, Osegon 97810	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Dearing and animated roll bookers of babaration content
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 20 ft.
Datama and Dutama D	
Cable	Static level 4 ft. below land surface. Date 3-2/-77
Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded   Welded V	(12) WELL LOG: Diameter of well below casing 8"
8 " Diam, from 6 ft. to 41 ft. Gage 250	Depth drilled 45 ft. Depth of completed well 45 ft.
ft. Gageft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated?   Yes M. No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Topsoil. 0 3
perforations fromft. toft.	Clay stone 4 boulders 3 11
perforations fromft. toft.	Srane 11 31
perforations from ft. to ft.	Basalr, broken, gray 31 45
(7) SCREENS: Well screen installed?   Yes N. No	
· · ·	
Manufacturer's Name	
Diam. Slot size Set from ft. to ft.	
Diam, Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
a pump test made?  Yes No If yes, by whom?	
: gal./min. with ft. drawdown after hrs.	
" " " "	- to the state of
air test 190 " 39 " 1"	
Oct.   100 gal./min. with 2   ft. drawdown after   hrs.	
	Work started 3-15 19 77 Completed 3-2/ 19 77
Temperature of water Depth artesian flow encountered ft.	
(9) CONSTRUCTION:	Date well drilling machine moved off of well 3-24 1977
Well seal—Material used Cement	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Anula Date 3/21, 19 77
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 46.5
How was cement grout placed?	Diffing Machine Operator's Literate 10
The state of the s	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?    Yes □ No Plugs Size: location ft.  Did any strata contain unusable water? □ Yes ■ No	Name TROY GRIFFIN (Person, firm or corporation) (Type or print)
· · · · · · · · · · · · · · · · · · ·	Address 900 HERNISTON AVE, HER MISTON OFE
Type of water? depth of strata	Frances Annual Control of the Contro
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed?  Yes No Size of gravel:	
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 3-21, 19.7.7