## WATER WELL REPORT UMAT STATE OF OREGON 1549

## RECEIVED

JUL 3 0 1984

State Well No.	4n	27E-25da
----------------	----	----------

State Permit No.

WATER RESOURCES DEPT

SALCI	II. OILLOUIA	
1) OWNER:	(10) LOCATION OF WELL:	
Name Mt Tahoma Leasing	11. 1.11.	33 - 1
Address PD BOX 99307		1 05-
City Tacoma State Wa	Tax Lot # Lot Blk	R. W.M. Subdivision
	Address at well location:	Capativiann
2) TYPE OF WORK (check):		
New Well → Deepening □ Reconditioning □ Abandon □ f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v	vell.
	Depth at which water was first found	95 ft.
		land surface. Date 7-25-8
Rotary Air Driven Domestic Industrial Municipal Cotary Mud Dug Irrigation Test Well Other Dustrial Withdrawal Reinfection		per square inch. Date
EL CACING INCTALLED.	(12) WELL LOG: Diameter of well below Depth drilled 44.3 ft. Depth of	w casing
5) CASING INSTALLED: Steel Plastic Welded Welded Discussion of the Gauge Diam from ft. to ft. Gauge	Formation: Describe color, texture, grain size and st thickness and nature of each stratum and aquifer per for each change of formation. Report each change in and indicate principal water-bearing strata.	ructure of materials; and show attracted, with at least one entry
LINER INSTALLED:		<del></del>
"Diam from 3 ft. to 543 ft. Gauge 564.40	MATERIAL	From To SWL
	Jan Sanda	0 4
6) PERFORATIONS: Perforated? Yes \( \text{No} \)	They Sand & Soul	15.436
Type of perforator used	Blue Class	42 85
in. by in. by in. 50 perforations from 323 ft. to 343 ft.	Black Basolt	85 112 55
perforations from 20. ft. to 27.2. ft. 50. perforations from 40.3 ft. to 42.3 ft.	Brown Busalt	1/2 /2/
perforations from	Black Basalt	121 135
	Tan Clay	135 188
7) SCREENS: Well screen installed? ☐ Yes 🖼 No	Black Bysalt	188 265
Manufacturer's Name	Grey Donalt	265281
Cype     Model No.       Diam.     Slot Size     Set from	VISI Ex lar Susult	28/285 66
Diam. Slot Size Set from ft. to ft.	Space Bursalt	285330
Drowdown is amount water level is leaved	Pille Grant	330 375
8) WELL TESTS:  Drawdown is amount water level is lowered below static level	Distance of the second	245 4/28
Vas a pump test made?   Yes  No If yes, by whom?	Benin Brait	425 438 WB
gal./min. with ft. drawdown after hrs.	Black Barnet	438 448
" " "		100
Air test S gal./min. with drill stem at 743 ft. 2 hrs.		
Bailer test gal/min. with ft. drawdown after hrs.		
rtesian flow g.p.m.		
berature of water Depth artesian flow encountered ft.	Work started # - 20 19 84 Comple	ted 7-25 1984
9) CONSTRUCTION: Special standards: Yes $\square$ No $\boxtimes$	Date well drilling machine moved off of well	7-25 1984
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct	supervision. Materials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my	best knowledge and belief.  Date 7 2 5 19
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	,
Number of sacks of cement used in well seal sacks  How was cement grout placed?	Drilling Machine Operator's License No	
The state of the s	Water Well Contractor's Certification:	-
The state of the s	This well was drilled under my jurisdiction	n and this report is true to
Vas pump installed? Type HP Depth ft.	the best of my knowledge and belief.	_1.11. 2
Was a drive shoe used? XYes \( \square\) No \( \text{Plugs} \) Size: location ft.	Name (Person, firm or corporation)	(Type or princ)
Did any strata contain unusable water?   Yes No	Address DO BOT 12 %	Hermiston
Type of Water? depth of strata	[Signed]	
Method of sealing strata off	(Water Well Contra	
Vas well gravel packed?     □ Yes No     Size of gravel:       Gravel placed from     ft. to     ft.	Contractor's License NoDate	7-25,19.55
MANTON PAROON ALVALL PROPERTY PROPERTY AND	1	