

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

UMAT 1602

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

#3

State Well No.

4W/28E-1ba

State Permit No.

(1) OWNER:

Name Gordon Westby
Address Melton St

(2) TYPE OF WORK (check):

New Well [ ] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [ ] Cable [ ] Dug [ ] Driven [ ] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [ ] Industrial [ ] Municipal [ ] Irrigation [ ] Test Well [ ] Other [ ]

CASING INSTALLED:

Threaded [ ] Welded [ ]

12" Diam. from 0 ft. to 0 ft. Gage
12" Diam. from 0 ft. to 0 ft. Gage
12" Diam. from 0 ft. to 0 ft. Gage

PERFORATIONS:

Perforated? [ ] Yes [ ] No.

Type of perforator used

Size of perforations in. by in.
perforations from 0 ft. to 0 ft.
perforations from 0 ft. to 0 ft.
perforations from 0 ft. to 0 ft.

(7) SCREENS:

Well screen installed? [ ] Yes [ ] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [ ] Yes [ ] No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? [ ] Yes [ ] No Plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [ ] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [ ] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wena Driller's well number
NE 1/4 NW 1/4 Section 1 T. 4 R. 28 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.
Static level ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled ft. Depth of completed well ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Contains handwritten entries: Sand 0-60, Sand clay 60-125, Sand gravel 125-134.

RECEIVED

APR 29 1992

WATER RESOURCES DEPT
SALEM, OREGON

Work started 19 Completed 19
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date, 19
(Drilling Machine Operator)

Drilling Machine Operator's License No. 352

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name J.A. Fredrickson
(Person, firm or corporation) (Type or print)

Address RT 2 Box 2066 Herz

[Signed] J.A. Fredrickson
(Water Well Contractor)

Contractor's License No. Date, 19