NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT UMAT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State	Well	No.	4/1	288-		12	
				1000	····}	<u></u>	~(

state Permit No.

(1) OWNER:	(10) LOCATION OF WELL:			
Name Coff Construction 7	County UMatilla Driller's well number			
Address fly Buy 148 Hrmillow &c	NA 14 SA14 Section T. 4N R. 28E W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well Deepening □ Reconditioning □ Abandon □	-			
If abandonment, describe material and procedure in Item 12.	(11) WATER FENTER C			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.			
Rotary Driven Domestic To Industrial To Manual To	Depth at which water was first found 56 ft. Static level /8 ft below land surface. Data 8-/6			
Cable Jetted John Irrigation Test Well Other	Static level / ft. below land surface. Date 8 - / 4 Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Threaded Welded	(19) YEAR TOO			
# Diam. from # 1 ft. to 57 ft. Gage 250	Diameter of wen below casing			
" Diam. fromft. toft. Gage				
ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,			
(6) PERFORATIONS: Perforated? ☐ Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used	MATERIAL From To SWL			
Size of perforations in. by in.	Soil Sandy 0 2			
perforations from ft. to ft.	Sand a Small shoul 2 56			
perforations from ft. to ft	Breek Sant Many 56 38 18			
	- Dicaro I			
(7) SCREENS: Well screen installed? Yes No				
Manufacturer's Name Model No				
Diam. Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	RECEIVED NICKIVED			
(8) WELL TESTS: Drawdown is amount water level is	SEP 17 1979 OCT 20 1979			
lowered below static level	WATER RESOURCES			
Was a pump test made? ☐ Yes No If yes, by whom?	WATER RESOURCES DEPT SALEM, OREGON			
nrs.	SALEM, OREGON			
" " "				
Bailer test 2.5 gol/min with 15 gran 1				
sian flow g.p.m. with χ it. drawdown after χ hrs.				
Temperature of water 34 Depth artesian flow encountered ft.	Work started & 11 to TA			
	Work started 8 - / 6 19 Completed 8 - 16 19 79 Date well drilling machine moved off of well 8 - 1 / 19 79			
(9) CONSTRUCTION: Well seal—Material used Rentonite	0 / 6 / 1			
Well sealed from land surface to	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.			
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well hore below seal	[Signed] Law sussell Date 8-16 1979			
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)			
How was coment grout placed? [wyglt]	Drilling Machine Operator's License No. 333			
by Bentomite Slynn of 6 MD	Water Well Contractor's Certification:			
Times	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	true to the best of my knowledge and belief			
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address Manning ore			
Method of sealing strata off	[Signed] day wisself			
Was well gravel packed? Tes No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No. 47.2 Date 8-16 19			