NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, UMAT SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

· I bd

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Ronald & + Jane a. Flink	County Umatilla Driller's well number
Address R+2 BW 2410	16 11 10 11 11 11 11 11 11 11 11 11 11 11
Hermister Oregon 97838	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	bearing and distance from security of subdivision corner
New Well □ Deepening ★ Reconditioning □ Abandon □	
bandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found
Rotary Driven Domestic Manustrial Municipal Domestic Municipal D	Static level 114' ft. below land surface. Date 8-10-79
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(10) MARKET TO C
"Mine Diam. from ft. to ft. Gage ft. Gage	Depth drilled 2 0 1 4 Parts of Well below casing
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Basalr, gray 203 233
perforations from ft. to ft.	Rock, red4 gleen classtone 233 240 W.B.
perforations from	Basalt, Alack / green blegatine 240 251
perforations from ft. to ft.	Rock, brown green classione 251 272
(7) SCREENS: Well screen installed? Yes No	Basar black yaren Claystone 272 330
Manufacturer's Name	Rock, browngilen eleptine 330 342 W.B.
Type Model No.	Basal, black 342 350 W.B.
Diam Slot size Set from ft. to ft.	Basalt, black green class tre 474 484
Slot size Set from ft. to ft.	Basalt, black 484 499 W.D.
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	RECEIVER
Yield: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " " "	AUG3 0 1979
MIRTEST 75 " 286 " "	WATER RESOURCES DEPT.
Bailer test 60 gal./min. with 186 ft. drawdown after hrs.	SALEM, OREGON
Artesian flow g.p.m. 166	
perature of water Depth artesian flow encountered ft.	Work started 8-8 1979 Completed 8-10 1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8-10 1979
Well seal-Material used not disturbed	
Well sealed from land surface toft.	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal in.	Waterials used and information reported above are true to my
Diameter of well bore below seal in.	best knowledge and belief.
Number of sacks of cement used in well sealsacks	[Signed] Machine Operator) Date 8-10, 19 79
How was cement grout placed?	Drilling Machine Operator's License No. 1210
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name TROY GRIFFIN (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 900 HERMISTON AVE HERMISTON, ORE
Method of sealing strata off	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] Joseph (Water Well/Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 8-10 , 1979