NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

8 1976 not write above this line)

STATE ENGINEER, SALEM, OREGOR 9710 C E V ESTATE OF OREGON within 30 days from the date of well completion.

State Well No.	4N/28E-1	
State Dermit M	······································	

(1) OWNER: WATER RESOURCES DEPT.	(10) LOCATION OF WELL:
Name T. L. Sseck SALEM, OREGON	County Thuatila Driller's well number
Address $RR.3$	14 14 Section 1 T. 4 M R. 28 E. W.M.
Hermiston, Pregon 97838	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check): √	
New Well Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 135 ft.
Rotary 🛪 Driven 🗆 Domestic 💆 Industrial 🗆 Municipal 🗆	Static level 77 ft. below land surface. Date /2-3-75
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded Company Diam from Company ft. to 155 ft. Gage 1250	(12) WELL LOG: Diameter of well below casing Depth drilled /55 ft. Depth of completed well /55 ft. Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Topsoil 0 2
perforations from ft. to ft.	Sand gray 2 132
perforations from ft. to ft.	Sand, flade 132 145
perforations from ft. to ft.	Sand Taravel 145 155 W.B.
(7) SCREENS: Well screen installed? Yes M No	
Manufacturer's Name	
Type Model No	
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes Ko If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	21 77 21 77
" " "	
n - n - n - n - n - n - n - n - n - n -	
Bailer-test / 0 0 gal./min. with 63 ft. drawdown after hrs.	
Artesian flow g.p.m.	
Crature of water Depth artesian flow encountered ft.	Work started 12-2 1975 Completed 12-3 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well /> - 3 19 75
Well seal—Material used	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 12/3, 19.75
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
Number of sacks of bentonite used in well seal sacks	Diffing Machine Operator's Intense 100.
Brand name of bentonite	Water Well Contractor's Certification:
of water	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes □ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 900 HERMISTOHAVE, HERMISTON OFF
Method of sealing strata off	Tan Haillia.
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 65 Date 12-3 1975