

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

UMAT 1731

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

APR 5 - 1976

State Well No. HN/28E-2

Permit No.

(1) OWNER:

Name Proctor & Smith
Address 115 Hermiston Ave
Hermiston Oregon 97838

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

(5) CASING INSTALLED:

8" Diam. from 0 ft. to 50 ft. Gage 1250
Threaded [] Welded [X]

PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
Bauer test 300 gal./min. with 20 ft. drawdown after 1 hrs.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 2.5 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 15 sacks
Number of sacks of bentonite used in well seal
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water
Was a drive shoe used? [X] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [X] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number
NW 1/4 NW 1/4 Section 2 T. 47N R. 28E. W.M.
Bearing and distance from section or subdivision corner
East 1/2

(11) WATER LEVEL: Completed well.

Depth at which water was first found 31 ft.
Static level 25 ft. below land surface. Date 3/29/76
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled 50 ft. Depth of completed well 50 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Topsoil, Sand, Claystone, blue, Gravel.

Work started 3-26 1976 Completed 3-29 1976
Date well drilling machine moved off of well 3-29 1976

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] James T. Leitch Date 3-29, 1976
(Drilling Machine Operator)
Drilling Machine Operator's License No. 665

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name TROY GRIFFIN (Type or print)
Address 900 HERMISTON AVE, HERMISTON ORE
[Signed] Troy Bluffin (Water Well Contractor)
Contractor's License No. 65 Date 3-29, 1976