

UMAT 1958

RECEIVED

SEP 4 1968

UMAT 1958

WATER WELL REPORT

STATE ENGINEER OF OREGON SALEM OREGON

State Well No. 4N/28-8 dd State Permit No.

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

G-4800

(1) OWNER:

Name Harold Rosenbaum Address Hermiston Oregon

(2) LOCATION OF WELL:

County Umatilla Driller's well number 1/4 Section 8 T. 44N. R. 22E W.M. Bearing and distance from section or subdivision corner App. 125' From W. Bank of Umatilla River

(3) TYPE OF WORK (check):

Well [] Deepening [x] Reconditioning [] Abandon [] In abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

(5) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(6) CASING INSTALLED:

Threaded [] Welded [] Diam. from ft. to ft. Gage

(7) PERFORATIONS:

Perforated? [] Yes [x] No Type of perforator used Size of perforations in. by in. perforations from ft. to ft.

(8) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Model No. Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Well seal—Material used in seal Depth of seal ft. Was a packer used? Diameter of well bore to bottom of seal in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [] Yes [] No Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft. Did any strata contain unusable water? [] Yes [x] No Type of water? Depth of strata Method of sealing strata off

(10) WATER LEVELS:

Static level 38 ft. below land surface Date 8-26-68 Artesian pressure lbs. per square inch Date

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Bailer test 40 gal./min. with 6 ft. drawdown after 1 hrs. Artesian flow g.p.m. Date 8-26-68 Temperature of water Was a chemical analysis made? [] Yes [x] No

(12) WELL LOG:

Diameter of well below casing 6" Depth drilled 107 ft. Depth of completed well 215 ft. Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

Table with columns: MATERIAL, FROM, TO. Rows: Basalt Dense (108-206), Vesicular Basalt (206-215), Water Bearing. Handwritten note: This well was drilled by others, 0-0 108

Work started 8-8-1968 Completed 8-23-1968 Date well drilling machine moved off of well 8-26-1968

(13) PUMP:

Manufacturer's Name Reda Type: SUBMERSIBLE H.P. 2

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME W.R. FILL (Person, firm or corporation) (Type or print) Address 222 N.E. 132 AVE PORTLAND Drilling Machine Operator's License No. 299 [Signed] J.R. Jell (Water Well Contractor) Contractor's License No. 405 Date 9-1, 1968

RECEIVED
SEP 4 1968
STATE ENGINEER
SALMON DIVISION

Ernest Ed L.
H. Rosenbaum

A tract of land located in the Southeast Quarter of Section 8, Township 4 North, Range 28, E. W. M., and lying West of the Umatilla River. Said tract being a portion of that tract of land described by Deed to Robert R. Dickenson and Daisy Fern Dickenson, husband and wife, in Deed Book 256, Page 590 of the Umatilla County Records. Being more particularly described as follows:

Beginning at a point on the South line of said Section 8, 850 feet West of the Southeast corner of said Section; thence North and parallel to the East line of said Section, a distance of 186 feet to the true point of beginning of this description; thence North 200 feet and parallel to the East line of said Section; thence East and parallel to the South line of said Section to the West bank of the Umatilla River at low water mark; thence Southeasterly along said low water mark to a point 186 feet North of the South line of said Section; thence West and parallel to the South line of said Section to the point of beginning;

ALSO, an easement for the purpose of ingress and egress over and across the following described premises, to-wit:

Commencing at the Southeast corner of Section 8, Township 4 North, Range 28, E. W. M.; thence due West along the South line of the said Section 8, a distance of 1061.00 feet to the point of beginning for the following description; thence North 0° 02' East a distance of 13 feet to the Southeast corner of a tract of land of 211.00 feet to the Southwesterly corner of a tract of land as it is conveyed in Book 267, Page 708 of the Deed Records of Umatilla County, Oregon; thence North 0° 02' East along the Westerly line of the said tract of land a distance of 20.00 feet; thence due West a distance of 231.00 feet; thence South 0° 02' West a distance of 206.00 feet to a point on the South line of the said Section 8; thence due East along the South line of the said Section 8, a distance of 20.00 feet to the point of beginning;

All being East of the Willamette Meridian, in the County of Umatilla and State of Oregon;

EXCEPTING any and all water rights of way and roads.