NOTICE TO WATER WELL CONTRACTOSTATE ENGINEER IN FEB 11 1966

The original and first copy of this report are to be

FALLY WATER WELL REPORTE ENGINEER IN O.

	1	CC	,
HN	128-	10年	

STATE ENGINEER, SALEM, OREGON 97310 TIMAT

Static level

Artesian pressure

STATE OF OREGONALEM OR

	1	CC
HN	128-	10£

within 30 days from the date of well completion.	(Please ty	pe or print) 6-3629 State Permit No		
(1) OWNER:		(11) WELL TESTS: Drawdown is amount v lowered below static le	vater level	is
Name Hermiston Medical Co	enter	Was a pump test made? ▼ Yes □ No If yes, by whom		
Address 975 Orchard Ave.		Yield: 85 gal./min. with 180 ft. drawdow		_
Hermiston, Ore.		" " " " "	/II alter	2 hrs.
(2) LOCATION OF WELL:		23 23		ñ
Garage (Imp. 1.22)	•	Bailer test gal./min. with ft. drawdo	wn after	hrs.
County Umatilla Driller's well	4 n. R. 28 E.W.M.	Artesian flow g.p.m. Date		
Hearing and distance from section or subdivis		Temperature of water Was a chemical analysis r	nade? 🔲 Y	es 🔏 No
rearing and distance from section of subdivis	ion comer	(12) WELL LOG: Diameter of well below ca	asing	8
		Depth drilled 207 ft. Depth of completed we		
	· · · · · · · · · · · · · · · · · · ·	Formation: Describe by color, character, size of materia show thickness of aquifiers and the kind and nature of stratum penetrated, with at least one entry for each cl	l and struc	ture, and
		stratum penetrated, with at least one entry for each cl	hange of f	ormation.
		MATERIAL	FROM	TO
(3) TYPE OF WORK (check):		Sand& gravel	0	14
Wel <b>K</b> □ Deepening □ Recon	ditioning	Clay brown	14	29
If abandonment, describe material and proce	dure in Item 12.	Sand & gravel	29	33
(4) PROPOSED USE (check):	(5) TYPE OF WELL:	Clay blue	33	38
Domestic   Industrial   Municipal	Rotary 🔲 Driven 🖂	Sand & gravel	38	49
36	Cable 💆 Jetted 🗌	Clay blue	49	62
	Dug 🗌 Bored 🗆		P.M62	75
(6) CASING INSTALLED: Thre	eaded 🗶 Welded 🗌	Rock gray hard	75	192
8" Diam. from 0 ft. to 60	0 ft. Gage	Rock black soft(water25@.P	. 192	199
ft. to	ft. Gage	Clay blue sandy min	199	203
		Rock black medium	203	207
(7) PERFORATIONS: Perfo	orated? 🗌 Yes 🙀 No			·
Type of perforator used	oranoa. El reg 💹 110	- Final Artis		<del></del>
Size of perforations in. by	in.			
perforations from				
perforations from				
perforations from	ft. to ft.			· · · · · · · · · · · · · · · · · · ·
perforations from	ft. to ft.			
perforations from	ft. to ft.			
(8) SCREENS: Well screen insta	alled? 🗌 Yes 🖈 No			
Manufacturer's Name	Les M. 140			
A Name	Andel No			
Diam Slot size Set from	**			
Diam Slot size Set from		Work started \$9-20 1965. Completed 11-	<u>-7-65</u>	19
(9) CONSTRUCTION:			<u>-7-65</u>	19
(b) Combined and the control of the		(13) PUMP:		
Well seal—Material used in seal	nent-	Manufacturer's Name		
Depth of sealft. Was a	packer used?	Туре: Н		
Diameter of well bore to bottom of seal				
Were any loose strata cemented off?   Yes Y	No Depth	Water Well Contractor's Certification:		-
Was a drive shoe used? ₹ Yes □ No		This well was drilled under my jurisdiction a	nd this r	eport is
==	ize of gravel:	true to the best of my knowledge and belief.		
Gravel placed from ft. to		NAME Ben Dreyer Drilling Contr	ractor	<u> </u>
Did any strata contain unusuable water?		NAME Ben Dreyer Drilling Contract Rt. I Bx 225 Hermiston, Address	or print)	
Type of water? depth of s  Method of sealing strata off	urata	Address	-	
(10) WATER LEVELS:		Drilling Machine Operator's License No7		••••••
CARLE V LELE VALLARIA TO	1	المعرب (عسر		

ft. below land surface

[Signed]