NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.



STATE OF OREGONS TATE ENGANGED 4N/28-11
(Please type or print)

(11) WELL

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is		
Name Leonard N. & June Crume	lowered below static level		
Address 445 E. Jennie Ave.	Was a pump test made? ☐ Yes K No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs.		
Hermiston, Oregon	rieid: gal./min, with ft. drawdown after hrs.		
(2) LOCATION OF WELL:	" " " "		
County Umatilla Driller's well number	Bailer test 20 gal./min. with noft. drawdown after 1 hrs.		
1/ Continu 1 1 m 41T - 00	Artesian flow g.p.m. Date		
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made? Yes No		
W690' of St of NEt of NW	(12) WELL LOG: Diameter of well below ca	sing 811	
	Depth drilled 32 ft. Depth of completed we	. 76	
	Formation: Describe by color, character, size of materia show thickness of aquifers and the kind and nature of a stratum penetrated, with at least one entry for each c	he material in each hange of formation.	
(a) mypr on word (MATERIAL		
(3) TYPE OF WORK (check):	Sandy soil	 	
Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	Fine gravel	5 14	
Lapandonment, describe material and procedure in Item 12.	Clay, brown	5 <u>14</u> 14 23	
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Fine gravel & sand	23 30	
Domestic ☒ Industrial ☐ Municipal ☐ Rotary ☐ Driven ☐	Sand - water	30 32	
Irrigation Test Well Other Cable I Jetted			
(6) CASING INSTALLED: Threaded To Welded Fix			
8 "Diam. from 0 ft. to 32 ft. Gage 250			
" Diam. fromft. toft. Gage			
(7) PERFORATIONS: Perforated? ☐ Yes K No			
Type of perforator used			
Size of perforations in. by in.			
perforations fromft. toftft.			
perforations fromft. toft.			
perforations fromft. toft.			
perforations fromft. toft.			
(e) SCREENS.			
Manufacturer's Name			
Model No. Slam. Slot size			
Diam. Slot size Set from ft. to ft.	Work started May 8 19 67 Completed May		
(9) CONSTRUCTION:		у 10 ₁₉ 67	
•	(13) PUMP:		
Well seal—Material used in seal bentonite Depth of seal 20 ft Was a nacker words 70	Manufacturer's Name		
Depth of seal 20 ft. Was a packer used? 110 Diameter of well bore to bottom of seal in.	Type:H	.P	
Were any loose strata-cemented off? Yes No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? A Yes No Depth			
Was well gravel packed? Yes No Size of gravel:	This well was drilled under my jurisdiction at true to the best of my knowledge and belief.	nd this report is	
Gravel placed fromft. toft.	Tohn Bonchor Woll Deilli		
Did any strata contain unusable water? Yes No			
Type of water? depth of strata	Address Rt 1, Box 552, Hermiston, Oregon		
Method of sealing strata off			
(10) WATER LEVELS:	Drilling Machine Operator's License No. 143		
Static level 6 ft below land surface Deta 5 /3 0 /6 m	[Signed] John Hersberg		
Anto-form and surface Date 1/0/	(Water Well Contractor)		
Artesian pressure lbs. per square inch Date	Contractor's License No. 315 Date 11 May	₁₉ 67	